

HPE D3610 - Storage enclosure

12 bays (SATA-600 / SAS-3) - HDD 10 TB x 12 - rack-mountable - 2U

Group	Storage
Manufacturer	HPE
Manufacturer item no.	Q1J14A
EAN/UPC	0190017176635



Description

HPE D3000 Enclosures 12 Gb SAS provides a higher level of redundancy and reliability, reducing single-points-of-failure within the storage network. The modular platform provides investment protection by allowing purchases based on your current need and future plans without hidden management fees.

The HPE D3000 Enclosures give you the flexibility to mix and match SAS, SATA and Solid State drives in the same enclosure, and extend the benefit of tiered storage to your customers.

Main features

Product Description	HPE D3610 - storage enclosure
Device Type	Storage enclosure
Enclosure Type	Rack-mountable - 2U
Max Supported Capacity	120 TB
Installed Devices / Modules Qty	12 (installed) / 12 (max)
Supported Drives	SATA-600 / SAS-3
Hard Drive	12 x 10 TB HDD SAS 12Gb/s Midline
Power	AC 120/230 V - 50/60 Hz
Power Redundancy	Yes
Dimensions (WxDxH)	44.8 cm x 59.8 cm x 8.7 cm
Weight	27.2 kg

Extended details

	General
Device Type	Storage enclosure
Enclosure Type	Rack-mountable - 2U
	Chassis
Installed Devices / Modules Qty	12
Supported Devices / Modules Qty	12
Supported Drives	SATA-600 / SAS-3
	Storage
Max Supported Capacity	120 TB
	Processor

CPU	No CPU
	Hard Drive
Type	HDD
Capacity	12 x 10 TB
Interface Type	SAS 12Gb/s
Spindle Speed	7200 rpm
Features	Midline
	Expansion / Connectivity
Expansion Bays	12 (total) / 0 (free) x hot-swap - 3.5" LFF
	Miscellaneous
Features	Redundant fans, firmware upgradable, 92% efficiency power supply
Cables Included	2 x mini SAS HD cable - 0.5 m
Included Accessories	Rack mounting kit, 2 x PDU interconnect cords
	Power
Power Device	2 x internal power supply - hot-plug
Max Supported Qty	2
Power Redundancy	Yes
Power Redundancy Scheme	1+1
Voltage Required	AC 120/230 V - 50/60 Hz
Power Consumption Operational	403 Watt
Power Provided	460 Watt
80 PLUS Certification	80 PLUS Gold
	Dimensions & Weight
Width	44.8 cm
Depth	59.8 cm
Height	8.7 cm
Weight	27.2 kg
	Manufacturer Warranty
Service & Support	Limited warranty - parts - 3 years Limited warranty - diagnosis - 3 years
	Environmental Parameters
Min Operating Temperature	10 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90%
Sound Emission	53 dBA

Technical data © 1WorldSync. Subject to technical modifications and errors.