

Epson EB-1470Ui - 3LCD projector

4000 lumens (white) - 4000 lumens (colour) - WUXGA (1920 x 1200) - 16:10 - 1080p - 802.11b/g/n wireless / LAN / Miracast - white

Group	Projectors
Manufacturer	Epson
Manufacturer item no.	V11H876040
EAN/UPC	8715946641034



Description

This interactive laser display solution eliminates the hassle and costs of maintenance while delivering impactful and collaborative meetings on a large scalable display to promote greater knowledge sharing and enhanced communication. Featuring finger-touch/dual-pen capability, Full HD WUXGA resolution, the ability to share two sources onto one display, and wireless and remote multi-location connectivity.

Main features

Product Description	Epson EB-1470Ui - 3LCD projector - 802.11b/g/n wireless / LAN / Miracast
Device Type	3LCD projector - 1080p
Colour	White
Built-in Devices	Speaker
Brightness (White)	4000 lumens
Brightness (Colour)	4000 lumens
Contrast Ratio	2500000:1 (dynamic)
Resolution	WUXGA (1920 x 1200)
Native Aspect Ratio	16:10
Colour Support	1.07 billion colours
Bulb type	Laser diode
Bulb life cycle	Up to 20000 hour(s) - normal mode Up to 30000 hour(s) - economic mode
Video Input	RGB, S-Video IEEE 802.11b/g/n wireless / LAN / Miracast
Speakers	Speaker(s) - integrated
Power	AC 230V (50 - 60 Hz)

Power Consumption Operational	448 Watt
Dimensions (WxDxH)	49.4 cm x 43.7 cm x 17.2 cm
Weight	11.4 kg

Extended details

	General
Device Type	3LCD projector - 1080p
Built-in Devices	Speaker
Networking	802.11b/g/n, Ethernet
Enclosure Colour	White
	Projector
Brightness (White)	4000 lumens
Brightness (Colour)	4000 lumens
Contrast Ratio	2500000:1 (dynamic)
Image Size	178 cm - 254 cm
Projection Distance	0.4 m - 0.6 m
Throw Ratio	0.27 - 0.37:1
Digital Zoom Factor	1.35x
Resolution	WUXGA - WUXGA (1920 x 1200)
Native Aspect Ratio	16:10
Colour Support	1.07 billion colours
Bulb type	Laser diode
Bulb life cycle	Up to 20000 hour(s) - normal mode Up to 30000 hour(s) - economic mode
Features	sRGB colour profile, EPSON 3LCD technology, Whiteboard Mode, Dynamic Mode, Theater Mode
	Lens
Focus Type	Manual
Lens Aperture	F/1.6
Keystone Correction Direction	Horizontal, vertical

Vertical Keystone Correction	-3 / +3
Horizontal Keystone Correction	-3 / +3
	Video Input
Analogue video Signal	RGB, S-Video
Video Interfaces	VGA, HDMI, composite video, MHL
LAN and Wireless Image Transferring Protocols	IEEE 802.11b, IEEE 802.11g, wired LAN, IEEE 802.11n, Miracast
	Speakers
Type	Integrated
Sound Output Mode	Mono
Output Power / Channel	16 Watt
Speakers	1 x mixed channel
	Expansion / Connectivity
Interfaces	1 x VGA input - 15 pin HD D-Sub (HD-15) 1 x Mobile High-Definition Link (MHL) / HDMI - 19 pin HDMI Type A 1 x HDMI input - 19 pin HDMI Type A 2 x USB 2.0 - 4 pin USB Type A 1 x USB 2.0 - 4 pin USB Type B 2 x audio line-in - mini-phone stereo 3.5 mm 1 x microphone 1 x audio line-out - mini-phone stereo 3.5 mm 1 x serial RS-232C 1 x network - RJ-45 1 x VGA output - 15 pin HD D-Sub (HD-15) 1 x Sync in 1 x Sync out 1 x DVI-D output 1 x composite video input - RCA 1 x remote control
	Miscellaneous
Included Accessories	Remote control, wireless LAN unit, pen case, interactive pens, pen tips
Cables Included	1 x USB cable
Mounting Kit	Included
	Power
Power Source	AC
Nominal Voltage	AC 230V (50 - 60 Hz)
Power Consumption Operational	448 Watt
Power Consumption Stand by	2 Watt
	Software / System Requirements

Software Included	Epson Easy Interactive Tools, EasyMP Multi PC Projection
Dimensions & Weight	
Width	49.4 cm
Depth	43.7 cm
Height	17.2 cm
Weight	11.4 kg
Manufacturer Warranty	
Service & Support	Limited warranty - 5 years / 12000 hours
Environmental Parameters	
Sound Emission	38 dBA
Sound Emission (Economic Mode)	27 dBA

Technical data © 1WorldSync. Subject to technical modifications and errors.