

Epson EB-725W - 3LCD projector

4000 lumens (white) - 4000 lumens (colour) - WXGA (1280 x 800) - 16:10 - 720p - ultra short-throw lens - 802.11a/b/g/n/ac wireless / LAN/ Miracast - white

Group Projectors

Manufacturer Epson

Manufacturer V11H999040 item no.

EAN/UPC 8715946681856



Description

With the EB-725W, users are no longer restricted to a single display size, with bright, large scalable options up to 120". Unlike flat-panel equivalents, there are no shadows, glare or blind spots, and the 4,000lm high-brightness laser light source can work when ambient lighting is also high. Multi-screen capability makes collaboration easy and intuitive, while a split-screen feature can show up to four inputs in one large display, preventing the need for additional displays.

The viewing experience is more immersive, with multiple connectivity options enhancing exceptional image and sound quality. For the ultimate in engagement, wireless connectivity, including Screen Mirroring via Miracast, allows everyone to share content from their tablets, mobiles or laptops. By connecting an optional Epson document camera you can also easily display images of 3D objects with incredible detail for the whole room to see.

Unlike flat panel displays, the EB-725W provides multiple display sizes and formats for one fixed cost. It also offers flexible mounting options to deploy a more comfortable view for delegates. When used with antibacterial whiteboards it provides a more hygienic workspace and is free from finger marks.

Sustainability is another strength, based on sustainable manufacturing, product usage and lifecycle.

Main features	
Product Description	Epson EB-725W - 3LCD projector - ultra short-throw - 802.11a/b/g/n/ac wireless / LAN/ Miracast - white
Device Type	3LCD projector - 720p
Colour	White
Built-in Devices	Speaker
Brightness (White)	4000 lumens
Brightness (Colour)	4000 lumens
Contrast Ratio	2500000:1 (dynamic)
Resolution	WXGA (1280 x 800)
Native Aspect Ratio	16:10
Colour Support	1.07 billion colours
Lens	Ultra short-throw lens
Bulb type	Laser
Bulb life cycle	Up to 20000 hour(s) - normal mode Up to 30000 hour(s) - economic mode
Video Input	IEEE 802.11a/b/g/n/ac wireless / LAN/ Miracast



Speakers	Speaker(s) - integrated
Environmental Standards	TCO Certified Projectors 8
Power	AC 230V (50 - 60 Hz)
Power Consumption Operational	255 Watt
Dimensions (WxDxH)	35.6 cm x 39.5 cm x 13.3 cm
Weight	5.7 kg

(WxDxH)	55.5 CH X 57.5 CH X 15.5 CH
Weight	5.7 kg
Extended details	
uetaits	
ъ . т	General
Device Type	3LCD projector - 720p
Built-in Devices	Speaker
Networking	802.11a/b/g/n/ac, Ethernet
Enclosure Colour	White
	Projector
Brightness (White)	4000 lumens
Brightness (Colour)	4000 lumens
Brightness (Reduced)	2800 lumens
Contrast Ratio	2500000:1 (dynamic)
Image Size	165.1 cm - 304.8 cm
Throw Ratio	0.28 - 0.37:1
Digital Zoom Factor	1.35x
Resolution	WXGA - WXGA (1280 x 800)
Native Aspect Ratio	16:10
Colour Support	1.07 billion colours
Max Sync Rate (V x H)	120 Hz
Bulb type	Laser
Bulb life cycle	Up to 20000 hour(s) - normal mode Up to 30000 hour(s) - economic mode
Features	sRGB colour profile, Blackboard Mode, EPSON 3LCD technology, Whiteboard Mode, Split Screen, Automatic Brightness Adjustment, Dynamic Lamp Control, Dynamic Mode, Theater Mode
	Lens
Туре	Ultra short-throw lens

Focus Type

Manual



Lens Aperture	F/1.6
Keystone Correction Direction	Horizontal, vertical
Vertical Keystone Correction	-3 / +3
Horizontal Keystone Correction	-3 / +3
	Video Input
Video Interfaces	VGA, HDMI, composite video
LAN and Wireless Image Transferring Protocols	IEEE 802.11b, IEEE 802.11g, wired LAN, IEEE 802.11a, IEEE 802.11n, Miracast, IEEE 802.11ac
	Speakers
Туре	Integrated
Sound Output Mode	Mono
Output Power / Channel	16 Watt
Speakers	1 x mixed channel
	Expansion / Connectivity
Interfaces	1 x audio line-out - mini-phone stereo 3.5 mm 3 x HDMI input - 19 pin HDMI Type A 1 x USB 2.0 - 4 pin USB Type A 2 x USB 2.0 - 4 pin USB Type B 3 x audio line-in - mini-phone stereo 3.5 mm 1 x microphone 1 x serial RS-232C - 9 pin D-Sub (DB-9) 2 x VGA input - 15 pin HD D-Sub (HD-15) 1 x network - RJ-45 1 x VGA output - 15 pin HD D-Sub (HD-15) 1 x composite video input - RCA
	Miscellaneous
Included Accessories	Wireless remote control
Cables Included	1 x USB cable
Security Features	Security lock slot (cable lock sold separately), password protection, control panel lock, Wireless LAN Lock
Security Slot Type	Kensington security slot
	Environmental Standards
TCO Certified	TCO Certified Projectors 8
	Power
Power Source	AC
Voltage Required	AC 230V (50 - 60 Hz)
Power Consumption Operational	255 Watt
Power Consumption Stand by	0.5 Watt



	Software / System Requirements
Software Included	Epson Projector Management Software, Epson iProjection
	Dimensions & Weight
Width	35.6 cm
Depth	39.5 cm
Height	13.3 cm
Weight	5.7 kg
	Manufacturer Warranty
Service & Support	Limited warranty - 5 years / 12000 hours - carry-in
	Environmental Parameters
Sound Emission	36 dBA
Sound Emission (Economic Mode)	26 dBA

Technical data © 1WorldSync. Subject to technical modifications and errors.