

HPE Platinum Plus Power Supply Kit

Power supply - hot-plug / redundant (plug-in module) - Common Slot
- 80 PLUS Platinum - AC 200-240 V - 1500 Watt - 1681 VA

Group	Power Supply
Manufacturer	HPE
Manufacturer item no.	684532-B21
EAN/UPC	4948382905338



Description

HPE Platinum Plus Power Supply Kit - Power supply - hot-plug / redundant (plug-in module) - Common Slot - 80 PLUS Platinum - AC 200-240 V - 1500 Watt - 1681 VA

Main features

Product Description	HPE Platinum Plus Power Supply Kit - power supply - hot-plug / redundant - 1500 Watt - 1681 VA
Device Type	Power supply - hot-plug / redundant - plug-in module
Specification Compliance	Common Slot
80 PLUS Certification	80 PLUS Platinum
Weight	1.36 kg
Input Voltage	AC 200-240 V
Power Capacity	1500 Watt / 1681 VA
Dimensions (WxDxH)	3.81 cm x 19.05 cm x 8.63 cm
Designed For	ProLiant DL560 Gen9, SL210t Gen8, SL230s Gen8, SL250s Gen8, SL270s Gen8

Extended details

	General
Device Type	Power supply - hot-plug / redundant - plug-in module
Specification Compliance	Common Slot
	Power Device
Input Voltage	AC 200-240 V
Input Voltage Range	AC 180 - 264 V
Frequency Required	50 - 60 Hz
Power Capacity	1500 Watt / 1681 VA
Efficiency	94%
80 PLUS Certification	80 PLUS Platinum
	Miscellaneous
Compliant Standards	FCC Class A certified, CSA, UL, TUV, C-Tick, BSMI, CCC, KCC, WEEE

Environmental Parameters	
Min Operating Temperature	5 °C
Max Operating Temperature	50 °C
Humidity Range Operating	5 - 95% (non-condensing)
Dimensions & Weight	
Width	3.81 cm
Depth	19.05 cm
Height	8.63 cm
Weight	1.36 kg
Dimensions & Weight (Shipping)	
Shipping Width	42.06 cm
Shipping Depth	14.61 cm
Shipping Height	18.75 cm
Shipping Weight	1.81 kg
Compatibility Information	
Designed For	HPE ProLiant DL560 Gen9 (1500 Watt), DL560 Gen9 Base (1500 Watt), DL560 Gen9 Entry (1500 Watt), DL560 Gen9 Performance (1500 Watt), SL210t Gen8 1U Node (1500 Watt), SL230s Gen8 1U Left Half Width Tray (1500 Watt), SL230s Gen8 1U Right Half Width Tray (1500 Watt), SL230s Gen8 Base 1U Left Tray Server (1500 Watt), SL230s Gen8 Base 1U Right Tray Server (1500 Watt), SL250s Gen8 2U Left Half Width Tray (1500 Watt), SL250s Gen8 2U PCIe Gen3 Left Tray (1500 Watt), SL250s Gen8 2U PCIe Gen3 Right Tray (1500 Watt), SL250s Gen8 2U Right Half Width Tray (1500 Watt), SL250s Gen8 Base 2U Left Half Width Tray (1500 Watt), SL250s Gen8 Base 2U Left Tray Server (1500 Watt), SL250s Gen8 Base 2U Right Half Width Tray (1500 Watt), SL250s Gen8 Base 2U Right Tray Server (1500 Watt), SL270s Gen8 1U Left Half Width Tray (1500 Watt), SL270s Gen8 1U Right Half Width Tray (1500 Watt), SL270s Gen8 Base 4U Left Half Width Tray (1500 Watt), SL270s Gen8 Base 4U Right Half Width Tray (1500 Watt), SL270s Gen8 SE 4U Left Tray (1500 Watt), SL270s Gen8 SE 4U Right Tray (1500 Watt)

Technical data © 1WorldSync. Subject to technical modifications and errors.