2-poorts HDMI splitter

DSP-2PH4-03

PERFECTE VERBINDING

- Stuur één HDMI signaal naar twee displays
- Verbeterde signaalkwaliteit door ingebouwde versterker
- Perfect voor thuisgebruik, onderwijsinstellingen en conferentiecentra



Kenmerken

- Stuurt één HDMI signaal naar twee verschillende monitoren, projectoren of TV's
- De digitale versterker vergroot de maximale transmissie-afstand tot ongeveer 10 meter en verbetert ook de signaalkwaliteit
- Geschikt voor 3D video

Specificaties

Ports: one input receptacle, 2 output HDMI output receptacles, 19 pin (A)
Interface standard: HDMI + HDCP v.1.4 (compatible with all HDMI versions)
Video formats: HDMI (480p/576i/576p/720p/1080i/1080P)
Maximal single-link range: 1920x1080 pixels, 1080p
Dual-link range: up to 3840x2160 at 30 Hz; color 30bit, 36bit

Supports Blue-Ray: 24/50/60fs/HD-DVD/xvYCC, audio DTS-HD/ Dolby-trueHD/DTS/Dolby-AC3/DSD/HD(HBR)
Signal retiming support
Working distance: up to 20 m at AWG26 HDMI cable (at 4K resolution 8 m input max, up to 12 m output)

Verpakking

Verpakkingshoeveelheid/stuks	45
Volume doos/CUM	0.02738
Gewicht doos/kg	3.79
Afmetingen productverpakking LxBxH:	120x25x180 mm
Afmetingen transportverpakking LxBxH:	370x370x200 mm
Land van herkomst	CN
Streepjescode	8716309091442
Douanecode	8517620000

Certificaat/Certificaten

Inhoud verpakking

Splitter
USB power cable
User manual

Copyright © 2009–2022, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588 | www.cablexpert.com | postmaster@cablexpert.com