

Mobotix Hemispheric Mx-c26B-AU-6N036

Network surveillance camera - dome - indoor - B&W (Day&Night) - 6 MP - 3072 x 2048 - audio - LAN 10/100 - MJPEG - H.264 - MxPEG - PoE

Group	Network Cameras
Manufacturer	Mobotix
Manufacturer item no.	MX-C26B-AU-6N036
EAN/UPC	4047438030571



Description

MOBOTIX Hemispheric Mx-c26B-AU-6N036 - Network surveillance camera - dome - indoor - B&W (Day&Night) - 6 MP - 3072 x 2048 - audio - LAN 10/100 - MJPEG, H.264, MxPEG - PoE

Main features

Product Description	MOBOTIX Hemispheric Mx-c26B-AU-6N036 - network surveillance camera - dome
Device Type	Network surveillance camera - fixed - dome - indoor
Audio	Yes: built-in speaker, built-in microphone
Camera Mount Type	Ceiling mount
Dimensions (WxDxH)	12 cm x 12 cm x 5.1 cm
Weight	212 g
Colour	White
Connectivity Technology	Wired
Camera	Black and white - Day&Night
Max Resolution	3072 x 2048
Frame Rate (max)	42 frames per second
Motion Detection	Yes
Optical Sensor Type	PS CMOS - 1/8" - 6 MP
Minimum Illumination	0.02 lux - B&W - shutter 1/60 sec 0.001 lux - B&W - shutter 1 sec
Lens Iris	F/1.8
Tilting Range (degree)	-5 to +45

Interfaces	Ethernet 10Base-T/100Base-TX
Voltage	PoE
Features	Motion sensor, progressive scanning, temperature sensor, tamper-detection, digital PTZ function, Privacy Zone, MxBus, MxActivitySensor, Multicast Streaming, Multi Stream Transport, ONVIF (Profile S) support, built-in DVR, MxAnalytics, master/slave functionality
Environmental Parameters (operating)	0 °C - 40 °C

Extended details

	General
Device Type	Network surveillance camera
Audio Support	Yes: built-in speaker, built-in microphone
Audio Formats	G.711, G.722
Form Factor	Dome
Camera Mount Type	Ceiling mount
Connectivity Technology	Wired
Width	12 cm
Depth	12 cm
Height	5.1 cm
Weight	212 g
	Camera
Type	Black and white - Day&Night - fixed - indoor
Digital Video Format	MJPEG, H.264, MxPEG
Max Digital Video Resolution	3072 x 2048
Motion Detection	Yes
Minimum Illumination	0.02 lux - B&W - shutter 1/60 sec 0.001 lux - B&W - shutter 1 sec
Video Capture	1280 x 720 @ 42 fps 1280 x 720 @ 25 fps
RAM	1 GB
Flash Memory	512 MB
Features	Motion sensor, progressive scanning, temperature sensor, tamper-detection, digital PTZ function, Privacy Zone, MxBus, MxActivitySensor, Multicast Streaming, Multi Stream Transport, ONVIF (Profile S) support, built-in DVR, MxAnalytics, master/slave functionality
	Image Sensor
Type	6 MP PS CMOS 1/8"
	Lens Construction
Lens Iris	F/1.8

Horizontal Field of View (degree)	103
Vertical Field of View (degree)	77
	Tilting
Range (degree)	-5 to +45
	Interfaces
Network Interface	Ethernet 10Base-T/100Base-TX
Network Protocols	DHCP, FTP, HTTP, NTP, SMTP, UDP/IP, SNMP, RTSP, RTP, HTTPS, IPv4, IPv6, FTPS, SIP
	Expansion / Connectivity
Ports	LAN/power - RJ-45 USB - Mini-USB Type B
Supported Memory Cards	microSD Card
	Miscellaneous
Compliant Standards	EN 61000-6-2, FCC CFR47 Part 15 B, IP20, EN 55024:2010, EN 55022:2010, AS/NZS CISPR22:2009+A1:2010, IK06, EN 55032:2012, EN 61000-6-3:2007+A1:2011, EN 61000-6-1:2007, EN 50121-4:2015, EN 61000-6-4:2007+A1:2011, IEEE 802.3af
Colour	White
	Power
Power Requirements	PoE
Power Device	5 Watt
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C

Technical data © 1WorldSync. Subject to technical modifications and errors.