

Poly RealPresence Group 500-720p Media Center 2RT65

Video conferencing kit - with EagleEye IV-12x camera

Group	Phones
Manufacturer	Poly
Manufacturer item no.	7200-67266-101
EAN/UPC	0610807791935



Description

The Polycom RealPresence Group 500 is ideal for conference rooms and other collaborative environments, from small meeting rooms to larger rooms with dual screens. Next-generation performance is combined with a simple user interface for an experience that will delight users while IT administrators will admire the compact design, broad interoperability, and the industry's lowest total cost of ownership.

Main features

Product Description	Poly RealPresence Group 500-720p Media Center 2RT65 - video conferencing kit - with EagleEye IV-12x camera
Device Type	Video conferencing kit
Localisation	Europe
Display	65" 1920 x 1080
Number Of Screens	2
Max Transfer Rate	6 Mbps
Digital Signaling Protocol	H.323, H.281, SIP, H.225, H.239, H.460
Data Compression Protocol	G.711, G.728, G.722, G.729.A, G.722.1
Video Input	Digital video camera
Video Output	Codec board - 1920 x 1200
Audio Input	Microphone
Input Device	Remote control (wireless)
Networking	Network adapter - Ethernet, Fast Ethernet, Gigabit Ethernet
Power	AC 120/230 V (60 Hz)
Bundled with	EagleEye IV-12x camera

Extended details

	General
Device Type	Video conferencing kit
Localisation	Europe
Bundled with	EagleEye IV-12x camera
	Display
Number Of Screens	2
Diagonal Size	65"
Native Resolution	1920 x 1080
Monitor Features	LED-backlit
	Modem
Type	Wired
Max Transfer Rate	6 Mbps
Digital Signaling Protocol	H.323, H.281, SIP, H.225, H.239, H.460
Data Compression Protocol	G.711, G.728, G.722, G.729.A, G.722.1
	Video Input
Type	Digital video camera (colour) - external
Digital Video Capture Resolution	1920 x 1080
	Video Output
Type	Codec board - external
Max External Resolution	1920 x 1200
Supported Display Graphics	VGA (640x480), XGA (1024x768), SXGA (1280x1024), SXGA+ (1400x1050), HDTV (1920x1080), WUXGA (1920 x 1200), HD (1280 x 720), WSXGA+ (1680 x 1050)
Digital Video Standard	High-Definition Multimedia Interface (HDMI)
	Audio Input
Type	Microphone - external
	Input Device
Type	Remote control

Connectivity Technology	Wireless
	Networking
Type	Network adapter
Connectivity Technology	Wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Features	Auto-uplink (auto MDI/MDI-X)
	Expansion / Connectivity
Interfaces	1 x video - VGA input - 15 pin D-Sub (DB-15) 1 x video - HDMI input - 19 pin HDMI Type A 1 x camera 2 x video - HDMI output - 19 pin HDMI Type A 2 x USB - 4 pin USB Type A 1 x audio - line-In - mini-phone stereo 3.5 mm 1 x serial - RS-232 - 8 PIN DIN 1 x audio - line-out - mini-phone stereo 3.5 mm 1 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45
	Power
Power Device	Power adapter - external
Voltage Required	AC 120/230 V (60 Hz)
	Manufacturer Warranty
Service & Support	Limited warranty - 1 year
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	15 - 80%

Technical data © 1WorldSync. Subject to technical modifications and errors.