

APC Smart-UPS X 2200 Rack/Tower LCD

UPS (rack-mountable / external) - AC 230 V - 1980 Watt - 2200 VA - RS-232 - USB - output connectors: 10 - 4U - black - for P/N: AR4018SPX432 - AR4024SP - AR4024SPX429 - AR4024SPX431 - AR4024SPX432 - NBWL0356A

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMX2200HV
EAN/UPC	0731304292609



Description

Maximizes battery performance, life, and reliability through intelligent, precision charging. Protects connected loads from surges, spikes, lightning, and other power disturbances.

Main features

Product Description	APC Smart-UPS X 2200 Rack/Tower LCD - UPS - 1980 Watt - 2200 VA
Device Type	UPS - rack-mountable / external
Rack Size	4U
Weight	38.64 kg
Input Voltage	AC 230 V
Output Voltage	AC 230 V
Power Capacity	1980 Watt / 2200 VA
Input Connectors	1 x power IEC 60320 C20
Output connectors	8 x power IEC 60320 C13 2 x power IEC 60320 C19
Battery	Lead Acid
Batteries Qty	1
Run Time (Up To)	9.8 min at full load
Networking	RS-232, USB
Colour	Black
Dimensions (WxDxH)	43.2 cm x 48.3 cm x 17.8 cm
Designed For	P/N: AR2487G, AR3100W, AR3105SP, AR3105W, AR3140G, AR3140W, AR3155W, AR3305W, AR3340G, AR3355SP, AR3355W, AR4000MVX429, AR4000MVX432, AR4018IX429, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4024IX431, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, NBWL0356A

Extended details

General	
Device Type	UPS - rack-mountable / external
Height (Rack Units)	4U

Colour	Black
Power Device	
UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 140 - 280 V
Frequency Provided	47 - 53 / 57 - 63 Hz
Frequency Required	50/60 Hz
Input Connectors	1 x power IEC 60320 C20
Power Output Connectors Details	8 x power IEC 60320 C13 2 x power IEC 60320 C19
Output Voltage	AC 230 V 47 - 53 / 57 - 63 Hz
Power Capacity	1980 Watt / 2200 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	645 Joules
Circuit Protection	Circuit breaker
Efficiency	98.1%
Battery	
Quantity	1
Technology	Lead Acid
Run Time (Up To)	9.8 min at full load 25.3 min at half load
Recharge Time	3 hours
Networking	
Remote Management Interface	RS-232, USB
Expansion / Connectivity	
Interfaces	1 x USB 1 x RS-232 1 x EPO (emergency power off)
Expansion Slots	1 (total) / 1 (free) x SmartSlot
Miscellaneous	
Cables Included	Serial cable USB cable Power cable 1.83 m
Rack Mounting Kit	Included
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), overload protection, cold-start function
Compliant Standards	CSA, C-Tick, GOST, UL 1449, UL 1778, VDE, IEC 60950, EN 50091-2, IRAM, RoHS, EN 50091-1, FCC Part 15 A, REACH
Software / System Requirements	
Software Included	APC PowerChute Business Edition
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C

Humidity Range Operating	0 - 95%
Sound Emission	55 dBA
Dimensions & Weight	
Width	43.2 cm
Depth	48.3 cm
Height	17.8 cm
Weight	38.64 kg
Dimensions & Weight (Shipping)	
Shipping Width	58.6 cm
Shipping Depth	63.3 cm
Shipping Height	33 cm
Shipping Weight	47.73 kg
Compatibility Information	
Designed For	P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC2513, ACF001, ACF002, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR202, AR203A, AR204A, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR3000, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3810, AR3812, AR3814, AR4000MV, AR4000MVX429, AR4000MVX432, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X431, AR4038X432, AR7007, AR7050, AR7057, AR8135BLK, NBWL0356A

Technical data © 1WorldSync. Subject to technical modifications and errors.