

HP LaserJet Enterprise M406dn

Printer - B/W - Duplex - laser - A4/Legal - 1200 x 1200 dpi - up to 40 ppm - capacity: 350 sheets - USB 2.0 - Gigabit LAN - USB 2.0 host

Group	Printers
Manufacturer	HP
Manufacturer item no.	3PZ15A#B19
EAN/UPC	0193905205998



Description

HP's entry-level Enterprise-class printer with speeds up to 42 ppm and strongest security. Workteams excel with HP's black-and-white office LaserJet printers, which pack extra punch with high-quality results, extra power, and more features. This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges.

Main features

Product Description	HP LaserJet Enterprise M406dn - printer - B/W - laser
Printer Type	Workgroup printer - laser - B/W
Number of Users	3-10 users
Weight	8.5 kg
Localisation	English, German, French, Italian, Spanish / Europe
Media Size Class	A4/Legal
Max Media Size	Legal (216 x 356 mm), A4 (210 x 297 mm)
Min Media Size (Custom)	76 mm x 127 mm
Max Media Size (Custom)	216 mm x 356 mm
Print Speed	Up to 38 ppm - B/W - A4 (210 x 297 mm) Up to 40 ppm - high speed - A4 (210 x 297 mm) Up to 40 ppm - B/W - ANSI A (Letter) (216 x 279 mm) Up to 42 ppm - high speed - ANSI A (Letter) (216 x 279 mm) Up to 31 ipm - B/W duplex - A4 (210 x 297 mm) Up to 33 ipm - B/W duplex - ANSI A (Letter) (216 x 279 mm)
Max Resolution (B&W)	1200 x 1200 dpi
Image Enhancement Technology	HP ProRes 1200 / HP FastRes 1200
Automatic Duplexing	Yes
Interface	USB 2.0, Gigabit LAN, USB 2.0 host
AirPrint Enabled	Yes
Processor	800 MHz
RAM Installed (Max)	1 GB (1 GB)
Flash Memory Installed (Max)	4 GB
Language Simulation	PCL 5, PostScript 3, PCL 6, PDF 1.7
Media Type	Envelopes, labels, plain paper, bond paper, recycled paper, light-weight paper, punched paper, preprinted paper, letterheaded paper, coloured paper

Total Media Capacity	350 sheets
Media Handling	100-sheet multipurpose tray, 250-sheet input tray
Monthly Duty Cycle (max)	100000 pages
Recommended Monthly Volume	900 - 4800 pages
Networking	Print server
Printer Features	Instant-on Technology, JetIntelligence Cartridge Technology
System Requirements	Microsoft Windows 7 Ultimate, Android, Microsoft Windows Server 2008 R2 x64 Edition, Apple iOS, Microsoft Windows Server 2012 x64 Edition, Windows 8.1, Microsoft Windows Server 2012 R2 x64 Edition, Microsoft Windows Server 2008 R2 SP1 (64-bits), Citrix XenServer 6.5, Windows 10, Microsoft Windows Server 2016 (64-bit), Citrix XenApp 7.6, Citrix XenDesktop 7.6, Apple macOS High Sierra 10.13, Apple macOS Mojave 10.14, Microsoft Windows Server 2019 (64-bit), Apple macOS Catalina 10.15
Environmental Standards	EPEAT Silver
Dimensions (WxDxH)	38.1 cm x 35.7 cm x 22 cm

Extended details

	General
Printer Type	Workgroup printer - laser - monochrome
Number of Users	3-10 users
Localisation	English, German, French, Italian, Spanish / Europe
	Printer
Print Speed	Up to 38 ppm - B/W - A4 (210 x 297 mm) Up to 40 ppm - high speed - A4 (210 x 297 mm) Up to 40 ppm - B/W - ANSI A (Letter) (216 x 279 mm) Up to 42 ppm - high speed - ANSI A (Letter) (216 x 279 mm) Up to 31 ipm - B/W duplex - A4 (210 x 297 mm) Up to 33 ipm - B/W duplex - ANSI A (Letter) (216 x 279 mm)
Built-in Devices	24-key pad, 2.7 inch LCD display
Connectivity Technology	Wired
Interface	USB 2.0, Gigabit LAN, USB 2.0 host
AirPrint Enabled	Yes
Max Resolution (B&W)	1200 x 1200 dpi
Image Enhancement Technology	HP ProRes 1200 / HP FastRes 1200
Automatic Duplexing	Yes
PostScript Support	Standard
First Print Out Time B/W	6.5 sec
Language Simulation	PCL 5, PostScript 3, PCL 6, PDF 1.7
Fonts Included	105 x TrueType 92 x PostScript 3
Printer Features	Instant-on Technology, JetIntelligence Cartridge Technology
Media Handling	100-sheet multipurpose tray, 250-sheet input tray
	Processor
Processor	800 MHz
	RAM
RAM (x 1 GB / 4 GB / 8 GB)	4 GB (4 GB / 8 GB)

	Flash Memory
Flash Memory	4 GB
	Media Handling
Media Type	Envelopes, labels, plain paper, bond paper, recycled paper, light-weight paper, punched paper, preprinted paper, letterheaded paper, coloured paper
Media Size Class	A4/Legal
Max Media Size	Legal (216 x 356 mm), A4 (210 x 297 mm)
Min Media Size (Custom)	76 mm x 127 mm
Max Media Size (Custom)	216 mm x 356 mm
Media Sizes	ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), A6 (105 x 148 mm), 100 x 150 mm, JIS B5 (182 x 257 mm), 101.6 x 152.4 mm, Statement (139.7 x 215.9 mm), 76 x 127 mm, 127 x 177.8 mm, Oficio (216 x 343 mm), 216 x 356 mm, 127 x 203.2 mm, JIS B6 (128 x 182 mm), RA4 (215 x 305 mm)
Envelope Sizes	US No 10 (104.7 x 241.3 mm), International DL (110 x 220 mm), International C6 (114 x 162 mm), International C5 (162 x 229 mm), International B5 (176 x 250 mm), Monarch (98.4 x 190.5 mm), US No 9 (98.6 x 225.6 mm), Japanese postcard (100 x 148 mm), Japanese Postcard Double (148 x 200 mm)
Media Weight	60 g/m ² - 175 g/m ²
Total Media Capacity	350 sheets
Media Feeders	1 x automatic - 100 sheets - Legal (216 x 356 mm) weight: 60 g/m ² - 175 g/m ² - (16 lbs (min) - 46.6 lbs (max)) 1 x automatic - 250 sheets - Legal (216 x 356 mm) weight: 60 g/m ² - 120 g/m ² - (16 lbs (min) - 32 lbs (max))
Max Media Capacity	900 sheets
Output Trays Capacity	150 sheets
	Duty Cycle
Monthly Duty Cycle (max)	100000 pages
Recommended Monthly Volume	900 - 4800 pages
	Networking
Networking	Print server
Remote Management Protocol	SNMP 2, SNMP 3, IPP, HTTP, HTTPS, SLP, DHCP, IPv4, IPv6
Security Protocols & Features	Kerberos, LDAP, SSL, Apple Bonjour, TLS, IPsec, 802.1x, EAP-TLS, PEAP
	Expansion / Connectivity
Connections	1 x USB 2.0 - 4 pin USB Type B 1 x Gigabit LAN 1 x USB 2.0 host - 4 pin USB Type A
	Miscellaneous
Consumables Included	1 x toner cartridge (black) - up to 3000 pages ISO/IEC 19798
Features	Security lock slot (cable lock sold separately), auto on/off, mercury free
Compliant Standards	FCC Class A certified, UL, cUL, GS, CECP, EN 62479:2010, IPsec/IKE, 21 CFR 1040.10, 21 CFR 1040.11, EN 61000-3-3:2013, CoC, CISPR 22:2008, EN 61000-3-2:2014, IEC 60950-1:2005 + A1:2009 + A2:2013, IEC 62479:2010, CAN/CSA C22.2 No. 60950-1-07 Second Edition 2011-12, FCC CFR47 Part 15 A, LVD 2014/35/EU, EN 55024:2010+A1:2015, EN 55032:2012, ICES-003 issue 6 Class A, EN 62368-1:2014, CISPR 32:2012, CISPR 35, EN 60825-1:2014, RAL-UZ 205, EN 55035:2017, IEC 62368-1: 2014, EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013, IEC 60825-1:2014 Class 1

Security Slot Type	Kensington security slot
	Power
Power Device	Power supply - internal
Frequency Required	50/60 Hz
Power Consumption Operational	531 Watt
Power Consumption Stand by	8.1 Watt
Power Consumption Sleep	1.2 Watt
	Software / System Requirements
OS Required	Microsoft Windows 7 Ultimate, Android, Microsoft Windows Server 2008 R2 x64 Edition, Apple iOS, Microsoft Windows Server 2012 x64 Edition, Windows 8.1, Microsoft Windows Server 2012 R2 x64 Edition, Microsoft Windows Server 2008 R2 SP1 (64-bits), Citrix XenServer 6.5, Windows 10, Microsoft Windows Server 2016 (64-bit), Citrix XenApp 7.6, Citrix XenDesktop 7.6, Apple macOS High Sierra 10.13, Apple macOS Mojave 10.14, Microsoft Windows Server 2019 (64-bit), Apple macOS Catalina 10.15
System Requirements Details	Windows 7/8.1/10 - HD 2 GB MacOS - HD 2 GB
	Environmental Standards
EPEAT Compliant	EPEAT Silver
Blue Angel	Yes
ENERGY STAR	Yes
	Manufacturer Warranty
Service & Support	Limited warranty - 1 year - on-site
	Environmental Parameters
Min Operating Temperature	15 °C
Max Operating Temperature	32.5 °C
Humidity Range Operating	10 - 90%
Sound Emission (Operating)	54 dBA
	Dimensions & Weight
Width	38.1 cm
Depth	35.7 cm
Height	22 cm
Weight	8.5 kg
	Dimensions & Weight (Shipping)
Width (Shipping)	44.3 cm
Depth (Shipping)	27.8 cm
Height (Shipping)	46.4 cm
Weight (Shipping)	11.37 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.