

Yealink SIP-T48U - VoIP phone with caller ID

10-way call capability - SIP - SIP v2 - SRTP - RTCP-XR - VQ-RTCPXR - classic gray

Group	Phones
Manufacturer	Yealink
Manufacturer item no.	SIP-T48U
EAN/UPC	6938818304321



Description

Yealink presents a dynamic business communication solution to executives and professionals with the new SIP-T48U IP phone. The phone employs an appealing large touch screen that makes the switch between pages and applications swift, easy and convenient. United Yealink Optima HD Voice technology and wideband codec of Opus, the T48U awards you the superb audio quality and crystal-clear voice communications. Moreover, the T48U puts dual USB ports in a phone that makes Bluetooth, Wi-Fi, USB headset and USB recording come true, and you can use any two of them freely according to your needs. The Yealink new T4U series offers the same elegant appearance as the T4 line, but with improvements for greater interoperability and better collaboration.

Main features

Product Description	Yealink SIP-T48U - VoIP phone with caller ID - 10-way call capability
Product Type	VoIP phone with caller ID
Main Features	Multiple VoIP protocol support, integrated Ethernet switch
VoIP Protocols	SIP, SIP v2, SRTP, RTCP-XR, VQ-RTCPXR
Voice Codecs	G.722, G.723.1, G.729ab, G.711a, G.726, iLBC, G.711μ
Speakerphone	Yes
Call Services	Voice Mail, Caller ID, Call Waiting, Call Forwarding, Call Transfer, Call Hold
Display	LCD display - colour - Yes
Network Ports Qty	2 x Ethernet 10Base-T/100Base-TX/1000Base-T
Body Colour	Classic gray

Extended details

General

Product Type	VoIP phone
Body Colour	Classic gray

Phone Features

Call Services	Voice Mail, Caller ID, Call Waiting, Call Forwarding, Call Transfer, Call Hold
Caller ID Type	Caller ID
Dialer Location	Base
Conference Call Capability	10-way

Speakerphone	Yes
Volume Control	Yes
Indicators	Message waiting indicator, call waiting indicator
Additional Functions	Call recording, Intercom, redial, mute, emergency call, auto answer, Do Not Disturb (DND), call return
	IP Telephony
Main Features	Multiple VoIP protocol support, integrated Ethernet switch
VoIP	Yes
VoIP Protocols	SIP, SIP v2, SRTP, RTCP-XR, VQ-RTCPXR
Voice Codecs	G.722, G.723.1, G.729ab, G.711a, G.726, iLBC, G.711μ
Quality of Service	IEEE 802.1Q (VLAN), IEEE 802.1p, Type of Service (ToS)
IP Address Assignment	DHCP, static
Security	IEEE 802.1X, TLS, SSL
Power Over Ethernet (PoE) Support	Yes
Network Protocols	TCP, TFTP, UDP, HTTP, DNS, HTTPS, SRTP, TR-069, SNTP
Network Ports Qty	2 x Ethernet 10Base-T/100Base-TX/1000Base-T
Voice Features	Comfort noise generation (CNG), voice activity detection (VAD), HD Voice, acoustic echo cancellation (AEC), packet loss concealment (PLC), adaptive jitter buffer (AJB), automatic gain control (AGC)
Network Features	Network Address Translation (NAT), Class 3 PoE, Lightweight Directory Access Protocol (LDAP), 16 VoIP accounts
	Phone Memory
Phone Directory Capacity	1000 names & numbers
	Display
Type	LCD display - colour
Display Location	Base
Diagonal Size	7"
Display Resolution	800 x 480 pixels
Colour Depth	24-bit (16.7 million colours)
Backlit	Yes
Display Languages	Multilingual
	Miscellaneous
Connections	Headset jack / RJ-9 2 x USB Handset jack / RJ-9
Placing / Mounting	Table-top
Cables Included	Ethernet cable - 2 m
Included Accessories	Stand
	Dimensions & Weight (Base)
Width	26.6 cm
Depth	22.6 cm

Height	18.5 cm
--------	---------

	Manufacturer Warranty
--	------------------------------

Service & Support	Limited warranty - 1 year
-------------------	---------------------------

Technical data © 1WorldSync. Subject to technical modifications and errors.