

Iiyama ProLite XU2494HS-B2 - LED monitor

24" (23.8" viewable) - 1920 x 1080 Full HD (1080p) @ 75 Hz - VA - 250 cd/m² - 3000:1 - 4 ms - HDMI - DisplayPort - speakers - matte black

Group	Flat Screens
Manufacturer	Iiyama
Manufacturer item no.	XU2494HS-B2
EAN/UPC	4948570120796



Description

The ProLite XU2494HS with a VA panel ensures accurate and consistent color reproduction with wide viewing angles. With a stylish slim bezel, the monitor would make an ideal choice for multi-monitor setups, compatible with any Iiyama dual or triple monitor arm accessory for bespoke workspace configurations. Equipped with speakers, headphone socket, HDMI and DisplayPort connections and a blue light reducer function to reduce eye fatigue, make this 24" XU2494HS-B2 display ideal for any office or home office application.

Main features

Product Description	Iiyama ProLite XU2494HS-B2 - LED monitor - Full HD (1080p) - 24"
Device Type	LED-backlit LCD monitor - 24"
Energy Class	Class E
Energy Consumption per Year	16 kWh
Power Consumption (On mode)	16.1 W
Panel Type	VA
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 75 Hz
Pixel Pitch	0.275 mm
Brightness	250 cd/m ²
Contrast Ratio	3000:1 / 80000000:1 (dynamic)
Response Time	4 ms (grey-to-grey)
Colour Support	16.7 million colours
Colour Gamut	72% NTSC, 96% sRGB
Input Connectors	HDMI, DisplayPort
Display Position Adjustments	Tilt
Screen Coating	Matte
Voltage	AC 100-240 V (50/60 Hz)
Colour	Matte black
Dimensions (WxDxH)	54 cm x 20 cm x 40.05 cm
Weight	3.2 kg

Compliant Standards	RoHS, WEEE, PSE Mark, REACH, TUV Bauart, ERP, VCCI Class B, EAC, 2012/19/EU, UKCA
---------------------	---

Extended details

	General
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class E
Energy Consumption per Year	16 kWh
Diagonal Size	24"
Viewable Size	23.8"
Panel Type	VA
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 75 Hz
Pixel Pitch	0.275 mm
Brightness	250 cd/m ²
Contrast Ratio	3000:1 / 80000000:1 (dynamic)
Colour Support	16.7 million colours
Colour Gamut	72% NTSC, 96% sRGB
Response Time	4 ms (grey-to-grey)
Horizontal Refresh Rate	30 - 85 kHz
Horizontal Viewing Angle	+89 / -89
Vertical Viewing Angle	+89 / -89
Screen Coating	Matte
Backlight Technology	LED backlight
OSD Languages	Czech, English, French, Italian, Polish, Spanish, Dutch, Japanese
Features	Eco-Mode, Flicker Free technology, i-Style Color, 3-sided micro-edge, Blue Light Reducer Function
Colour	Matte black
Dimensions (WxDxH)	54 cm x 20 cm x 40.05 cm
Weight	3.2 kg
	Audio
Type	Speakers - stereo
Output Power / Channel	2 Watt
	Connectivity
Interfaces	HDMI (HDCP) DisplayPort (HDCP)
	Mechanical
Display Position Adjustments	Tilt
Tilt Angle	-4/+22
VESA Mounting Interface	100 x 100 mm
	Miscellaneous

Features	Security lock slot (cable lock sold separately), VESA interface support
Cables Included	1 x HDMI cable
Compliant Standards	RoHS, WEEE, PSE Mark, REACH, TUV Bauart, ERP, VCCI Class B, EAC, 2012/19/EU, UKCA
Security Slot Type	Kensington security slot
Power	
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption (On mode)	16.1 W
Power Consumption SDR (On mode)	16 kWh/1000h
Power Consumption (Typical)	19 Watt
Power Consumption Stand by	0.5 Watt
Power Consumption (Off Mode)	0.3 Watt
Dimensions & Weight (Shipping)	
Shipping Width	61.3 cm
Shipping Depth	40.3 cm
Shipping Height	12.5 cm
Shipping Weight	4 kg
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years

Technical data © 1WorldSync. Subject to technical modifications and errors.