

APC Smart-UPS X 3000 Rack/Tower LCD

UPS (rack-mountable / external) - AC 230 V - 2700 Watt - 3000 VA - Ethernet 10/100 - RS-232 - USB - output connectors: 10 - 4U - black - with APC UPS Network Management Card AP9631 - for P/N: AR4018SPX432 - AR4024SP - AR4024SPX429 - AR4024SPX431 - AR4024SPX432 - NBWL0356A

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMX3000HVNC
EAN/UPC	0731304292623



Description

Intuitive LCD interface provides clear and accurate information in multiple languages with the ability to configure the UPS locally with easy to use navigation keys.
 High frequency design reduces or eliminates bulky transformers resulting in lighter units for ease of handling.
 APC Smart-UPS X 3000 Rack/Tower LCD recognizes when external battery packs are attached and automatically adjusts runtime.
 Patent-pending operating mode bypasses unused electrical components in good power conditions to achieve very high operating efficiency without sacrificing any protection.

Main features

Product Description	APC Smart-UPS X 3000 Rack/Tower LCD - UPS - 2700 Watt - 3000 VA - with APC UPS Network Management Card AP9631
Device Type	UPS - rack-mountable / external
Rack Size	4U
Weight	38.64 kg
Input Voltage	AC 230 V
Output Voltage	AC 230 V
Power Capacity	2700 Watt / 3000 VA
Input Connectors	1 x power IEC 60320 C20
Output connectors	8 x power IEC 60320 C13 2 x power IEC 60320 C19
Battery	Lead Acid
Batteries Qty	1
Run Time (Up To)	6.3 min at full load
Networking	Ethernet 10/100, RS-232, USB
Remote Management Protocol	SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, SSH, SSH-2
Colour	Black
Dimensions (WxDxH)	43.2 cm x 48.3 cm x 17.8 cm
Bundled with	APC UPS Network Management Card AP9631

Designed For	P/N: AR2487G, AR3100W, AR3105SP, AR3105W, AR3140G, AR3140W, AR3155W, AR3305W, AR3340G, AR3355SP, AR3355W, AR4000MVX429, AR4000MVX432, AR4018IX429, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4024IX431, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, NBWL0356A
--------------	--

Extended details

	General
Device Type	UPS - rack-mountable / external
Height (Rack Units)	4U
Colour	Black
Bundled with	APC UPS Network Management Card AP9631
	Power Device
UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 140 - 280 V
Frequency Provided	47 - 63 Hz
Frequency Required	47 - 63 Hz
Input Connectors	1 x power IEC 60320 C20
Power Output Connectors Details	8 x power IEC 60320 C13 2 x power IEC 60320 C19
Output Voltage	AC 230 V 47 - 63 Hz
Power Capacity	2700 Watt / 3000 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	645 Joules
Circuit Protection	Circuit breaker
Efficiency	98.5%
	Battery
Quantity	1
Technology	Lead Acid
Run Time (Up To)	6.3 min at full load 15.7 min at half load
Recharge Time	3 hours
	Networking
Remote Management Interface	Ethernet 10/100, RS-232, USB
Remote Management Protocol	SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, SSH, SSH-2
	Expansion / Connectivity
Interfaces	1 x USB 1 x RS-232 1 x EPO (emergency power off) 1 x management (Ethernet) - RJ-45
Expansion Slots	1 (total) / 0 (free) x SmartSlot
	Miscellaneous
Cables Included	Serial cable USB cable Power cable 1.83 m

Rack Mounting Kit	Included
Features	Audible alarm, LCD display, overload protection
Compliant Standards	CSA, C-Tick, GOST, UL 1449, UL 1778, VDE, IEC 60950, EN 50091-2, IRAM, RoHS, EN 50091-1, FCC Part 15 A, REACH
	Software / System Requirements
Software Included	APC PowerChute Business Edition
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	55 dBA
	Dimensions & Weight
Width	43.2 cm
Depth	48.3 cm
Height	17.8 cm
Weight	38.64 kg
	Dimensions & Weight (Shipping)
Shipping Width	58.6 cm
Shipping Depth	63.3 cm
Shipping Height	33 cm
Shipping Weight	47.73 kg
	Compatibility Information
Designed For	P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC2513, ACF001, ACF002, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR202, AR203A, AR204A, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR3000, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR3810, AR3812, AR3814, AR4000MV, AR4000MVX429, AR4000MVX432, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X431, AR4038X432, AR7007, AR7050, AR7057, AR8135BLK, NBWL0356A

Technical data © 1WorldSync. Subject to technical modifications and errors.