

AXIS M3057-PLVE Mk II Network Camera

6 MP outdoor-ready dome with 360° panoramic view

With its 6 MP sensor, AXIS M3057-PLVE Mk II offers excellent image quality and a complete 180° or 360° overview, indoors or out, around the clock. Perfect for video analytics, this compact mini dome also offers dewarped views such as panorama, quad, corner, and corridor views directly from the camera. It includes Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging light or near darkness. And, Axis OptimizedIR allows for surveillance in pitch darkness. Furthermore, enhanced security functionality prevents unauthorized access and safeguards your system.

- > [Complete 180° and 360° overview](#)
- > [Lightfinder, Forensic WDR, and OptimizedIR](#)
- > [Digital PTZ and dewarped views](#)
- > [Factory-focused with digital roll](#)
- > [Enhanced security features](#)



AXIS M3057-PLVE Mk II Network Camera

Camera		Onscreen controls	Day/night shift Wide dynamic range Video streaming indicator IR illumination
Image sensor	1/1.8" progressive scan RGB CMOS	Analytics	Included AXIS Video Motion Detection, active tampering alarm Supported AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, AXIS People Counter, AXIS Occupancy Estimator, AXIS Queue Monitor Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap
Lens	1.56 mm, F2.0 Horizontal field of view: 183° Vertical field of view: 183° Fixed iris, fixed focus, IR corrected	Event conditions	Analytics, edge storage events, virtual inputs through API, supervised external inputs, open casing
Day and night	Automatically removable infrared-cut filter	Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation, zoom preset, day/night mode
Minimum illumination	Color: 0.16 lux at 50 IRE, F2.0 B/W: 0.03 lux at 50 IRE, F2.0 0 lux with IR illumination on	Data streaming	Event data
Shutter speed	1/16000 s to 1 s	Built-in installation aids	Pixel counter, digital roll, repositioning of quad views, digital PTZ of view areas, digital PT of panorama, corner, corridor and quad views
Camera angle adjustment	Digital roll: ± 180°	General	
Video		Casing	IP66-, NEMA 4X- and IK10-rated Polycarbonate hard coated dome Aluminum Color: white NCS S 1002-B For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner.
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	Sustainability	PVC free
Resolution	Overview: 2016x2016 to 160x160 Panorama: 2560x1440 to 192x72 Double Panorama: 2560x1920 to 384x288 Quad view: 2560x1920 to 384x288 View area 1-4: 1920x1440 to 256x144 Corner right/left: 2368x1184 to 384x288 Double corner: 2016x2016 to 384x288 Corridor: 2560x1920 to 256x144	Memory	1024 MB RAM, 512 MB Flash
Frame rate	360° overview only, up to 2016x2016 without WDR: 50/60 fps @ 50/60 Hz 360° overview and dewarped views up to max resolution with WDR: up to 25/30 fps @ 50/60 Hz	Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 8.0 W, max 11.9 W
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265	IR illumination	Optimized IR with power-efficient, long-life 850 nm IR LEDs Range of reach 20 m (66 ft) or more depending on scene
Multi-view streaming	360° overview, dewarped panorama, corridor, corner left/right and quad views. Up to 4 individually cropped out and dewarped view areas. All different views can be streamed simultaneously. When streaming 4 dewarped view areas and one 360° overview in max resolution: up to 19 fps per stream.	Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Image settings	Compression, color saturation, brightness, sharpness, contrast, local contrast, white balance, day/night threshold, tone mapping, exposure control (including automatic gain control), exposure zones, Forensic WDR: up to 120 dB depending on scene, fine tuning of low-light behavior, dynamic text and image overlay, mirroring, digital roll, polygon privacy masks	Operating conditions	-40 °C to 50 °C (-40 °F to 122 °F) Start-up temperature: -30 °C to 50 °C (-22 °F to 122 °F) Maximum temperature (intermittent): 55 °C (131 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Humidity 10–100% RH (condensing)
Pan/Tilt/Zoom	Digital PTZ, preset positions Limited guard tour, control queue, on-screen directional indicator Tour recording (max 10, max duration 16 minutes each), guard tour (max 100), adjustable zoom speed	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5-95% RH (non-condensing)
Network		Approvals	EMC EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 Safety IEC/EN/UL 60950-22, IEC/EN/UL 62368-1, IEC/EN 62471 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, 60068-2-78, IEC/EN 60529 IP66, IEC/EN 62262 IK10, IEC 60721-3-5 Class 5M3 (vibration and shock), NEMA 250 Type 4X, NEMA TS 2-2016 Network IPv6 USGv6, NIST SP500-267
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, Axis Edge Vault with Axis device ID	Dimensions	Height: 66 mm (2.5 in) ø 149 mm (5.8 in)
Supported protocols	IPv6 USGv6, HTTP, HTTPS ^a , HTTP/2, SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, SIP, LLDP, MQTT v3.1.1, Syslog	Weight	700 g (1.5 lb)
System integration			
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Guardian with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S, ONVIF [®] Profile T specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX		

Included accessories	Installation guide, Windows® decoder 1-user license, drill hole template, cable gaskets, connector guard, I/O connector, RESISTORX® TR20 bit, mounting bracket, cable hole lid, view protector	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese
Optional accessories	AXIS T94T02D Pendant kit with weathershield AXIS Surveillance Cards AXIS TM3808-E Skin Cover Black AXIS Mounts Et Cabinets AXIS T6101 Audio and I/O Interface AXIS T6112 Audio and I/O Interface AXIS T94S02L Recessed Mount Kit For more accessories, see axis.com	Warranty	5-year warranty, see axis.com/warranty
Video management software	AXIS Device Manager, AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms		a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i> Environmental responsibility: axis.com/environmental-responsibility