

ViewSonic ViewBoard IFP4320 - 43" Diagonal Class (42.51" viewable) LED-backlit LCD display

interactive - with touchscreen (multi touch) - 4K UHD (2160p) 3840 x 2160

Group	Flat Screens
Manufacturer	ViewSonic
Manufacturer item no.	IFP4320
EAN/UPC	0766907010206



Description

Featuring 4K Ultra HD resolution and an advanced, next-generation touchscreen, the ViewSonic ViewBoard IFP4320 is perfect for small collaboration spaces in hybrid work environments. With a 43" high-accuracy in-cell touchscreen, this ViewBoard display delivers a smooth handwriting and annotation experience ideal for home offices, workplace cubicles, huddle spaces and more. Integrated myViewBoard annotation software and ViewBoard Cast streaming software, allow users to remotely collaborate with team members in any location. What's more, USB-C connectivity allows for quick and easy connection to laptops and PCs so that the IFP4320 can function as a primary touchscreen device.

Main features

Product Description	ViewSonic ViewBoard IFP4320 43" Class (42.51" viewable) LED-backlit LCD display - 4K
Product Type	LED-backlit LCD flat panel display with touchscreen (multi touch)
Diagonal Class	43"
Diagonal Size	42.51"
Commercial Use	Yes - interactive
Resolution	3840 x 2160
Display Format	4K UHD (2160p)
Frame Rate & Enhancement Technology	60 Hz Refresh Rate
Video Interface	Composite, HDMI
HDMI Ports Qty	1 ports
Connectivity	LAN
PC Interface	DisplayPort, RCA (composite)
LCD Backlight Technology	LED backlight
Image Aspect Ratio	16:9
TV Tuner	No tuner
Speaker System	2 speakers
Storage Capacity	16GB eMMC
USB	Yes

Included Accessories	Remote control, remote control, batteries, 8 x screws
Voltage	AC 100-240 V
Energy Class	Class G
Power Consumption Operational	120 Watt
Power Consumption Stand by	0.5 Watt
Dimensions (WxDxH)	96.7 cm x 5.57 cm x 55.81 cm
Weight	17.83 kg
Environmental Standards	ENERGY STAR Qualified

Extended details

	General
Product Type	LED-backlit LCD flat panel display
Energy Class	Class G
Power Consumption (Max)	150 Watt
Power Consumption Operational	120 Watt
Power Consumption SDR (On mode)	90 kWh/1000h
Diagonal Class	43"
Diagonal Size	42.51"
Commercial Use	Yes - interactive
Combined With	Touchscreen (multi touch)
TV Tuner	No tuner
TV Tuner Presence	No
Video Interface	Composite, HDMI
HDMI Ports Qty	1 ports
PC Interface	DisplayPort, RCA (composite)
Width	96.7 cm
Depth	5.57 cm
Height	55.81 cm
Weight	17.83 kg
	Display
Resolution	3840 x 2160
Display Format	4K UHD (2160p)
Image Aspect Ratio	16:9
Frame Rate & Enhancement Technology	60 Hz Refresh Rate
LCD Backlight Technology	LED backlight
Coating	Anti-glare
Image Contrast Ratio	1000:1
Brightness	350 cd/m²

Viewing Angle	178 degrees
Viewing Angle (Vertical)	178 degrees
Touchpoints Qty	10
Response Time	9 ms
Backlight Life	50,000 hour(s)
Features	Palm Rejection, Object Awareness, In-Cell Touch
Stands & Mounts	
Flat Panel Mount Interface	400 x 400 mm
VESA Compatibility	Yes
Media Player	
USB Port	Yes
Configuration	ARM Cortex-A73 Dual-Core + ARM Cortex-A53 Dual-Core - 3 GB LPDDR4 - 16GB eMMC
Operating System	Android OS 8.0
Remote Control	
Type	Remote control
Audio System	
Speaker System	2 speakers
Output Power / Total	20 Watt
Speakers	2 x main channel speaker - 10 Watt
Network & Internet Multimedia	
Connectivity	LAN
LAN Protocol	Gigabit Ethernet
Connections	
Connector Type	HDMI input DVI-D input USB 3.1 LAN Composite video input USB 2.0 DisplayPort Audio line-in RS-232 SPDIF output Audio line-out
Miscellaneous	
Included Accessories	Remote control, batteries, 8 x screws
Cables Included	A/V cable USB cable HDMI cable
Compliant Standards	CB, FCC, RoHS, WEEE, cTUVus, ERP, CE/EMC, Mexico Energy label
Environmental Standards	
ENERGY STAR Certified	Yes
Power	
Power Device	Power supply
Input Voltage	AC 100-240 V
Power Consumption Stand by	0.5 Watt
Manufacturer Warranty	
Service & Support	Limited warranty - parts and labour - 3 years - on-site Limited warranty - backlight - 3 years - on-site
Dimensions & Weight (Shipping)	
Width (Shipping)	120 cm

Depth (Shipping)	21 cm
Height (Shipping)	78.5 cm
Weight (Shipping)	22.45 kg
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	20 - 80% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.