

WD Ultrastar Data102 SE4U102-102

Storage enclosure - 1224 TB - 102 bays (SAS-3) - HDD 12 TB x 102 - rack-mountable - 4U

Group	Storage
Manufacturer	WD
Manufacturer item no.	1ES0311



Description

WD Ultrastar Data102 SE4U102-102 - Storage enclosure - 1224 TB - 102 bays (SAS-3) - HDD 12 TB x 102 - rack-mountable - 4U

Main features

Product Description	WD Ultrastar Data102 SE4U102-102 - storage enclosure
Device Type	Storage enclosure
Enclosure Type	Rack-mountable - 4U
Total Array Capacity	1224 TB
Max Supported Capacity	1224 TB
Installed Devices / Modules Qty	102 (installed) / 102 (max)
Supported Drives	SAS-3
Hard Drive	102 x 12 TB HDD SAS 12Gb/s - hot-swap - Secure Erase function, 512e Crypto
Power	AC 230V - 50/60 Hz
Power Redundancy	Yes
Dimensions (WxDxH)	44.7 cm x 104.7 cm x 17.5 cm
Weight	118.8 kg

Extended details

	General
Device Type	Storage enclosure
Enclosure Type	Rack-mountable - 4U
	Chassis
Installed Devices / Modules Qty	102
Supported Devices / Modules Qty	102
Supported Drives	SAS-3
	Storage
Total Array Capacity	1224 TB
Max Supported Capacity	1224 TB

	Processor
CPU	No CPU
	Hard Drive
Type	HDD - hot-swap
Capacity	102 x 12 TB
Interface Type	SAS 12Gb/s
Features	Secure Erase function, 512e Crypto
	Expansion / Connectivity
Expansion Bays	102 (total) / 0 (free) x hot-swap - 3.5"
Interfaces	6 x SAS 12Gb/s - 36 pin 4x Mini SAS HD (SFF-8644)
	Miscellaneous
Features	SCSI Enclosure Services 3 (SES3)
	Power
Power Device	2 x internal power supply - hot-plug
Power Redundancy	Yes
Power Redundancy Scheme	1+1
Voltage Required	AC 230V - 50/60 Hz
Power Provided	1600 Watt
	Dimensions & Weight
Width	44.7 cm
Depth	104.7 cm
Height	17.5 cm
Weight	118.8 kg
	Manufacturer Warranty
Service & Support	Limited warranty - 5 years
	Environmental Parameters
Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	8 - 80% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.