

HPE StoreEver LTO-8 Ultrium 30750

Tape drive - LTO Ultrium (12 TB / 30 TB) - Ultrium 8 - SAS-2 - internal
 - 5.25" - encryption

Group	Floppys & Streamer
Manufacturer	HPE
Manufacturer item no.	BC022A
EAN/UPC	0190017217734



Description

HPE StoreEver LTO Ultrium tape drives provide easy-to-enable security to protect sensitive data and prevent unauthorized access of tape cartridges.

Main features

Product Description	HPE StoreEver LTO-8 Ultrium 30750 - tape drive - LTO Ultrium - SAS-2
Device Type	Tape drive
Recording Standard	LTO Ultrium 8
Enclosure Type	Internal
Interface Type	SAS-2
Key Features	Encryption
Dimensions (WxDxH)	14.5 cm x 20.6 cm x 4.1 cm
Weight	1.45 kg
Colour	Black
Storage Removable	LTO Ultrium - 5.25" x 1/2H
Storage Removable Capacity	12 TB (native) / 30 TB (compressed)
Supported Tape Cartridges (Read and Write)	Ultrium 7, Ultrium 8
Data Transfer Rate (native)	300 MBps
OS Required	IBM AIX, SunSoft Solaris, HP-UX, Red Hat Linux, SuSe Linux, Microsoft Windows, HP Tru64 UNIX

Extended details

General	
Device Type	Tape drive - LTO Ultrium
Recording Standard	LTO Ultrium 8
Enclosure Type	Internal
Interface Type	SAS-2
Key Features	Encryption
Enclosure Colour	Black

Width	14.5 cm
Depth	20.6 cm
Height	4.1 cm
Weight	1.45 kg
Storage Removable	
Type	LTO Ultrium - 5.25" x 1/2H
Capacity	12 TB (native) / 30 TB (compressed)
Supported Tape Cartridges (Read and Write)	Ultrium 7, Ultrium 8
Recording Standard	Ultrium 7, Ultrium 8
Data Transfer Rate (native)	300 MBps
Average Seek / Access Time	15 sec
Buffer Size	1024 MB
Expansion / Connectivity	
Interfaces	1 x SAS 6Gb/s - 29 pin internal SAS (SFF-8482)
Compatible Bay	1 x front accessible - 5.25" x 1/2H
Miscellaneous	
Cables Included	1 x mini SAS cable
MTBF	250,000 hour(s)
Compliant Standards	TUV, VCCI, C-Tick, BSMI, GOST, EN 60950, NOM, RRL, IEC 60950, CB, FCC CFR47 Part 15, cCSAus, CAN/CSA C22.2 No. 60950
Software / System Requirements	
Software Included	Drivers & Utilities
OS Required	IBM AIX, SunSoft Solaris, HP-UX, Red Hat Linux, SuSe Linux, Microsoft Windows, HP Tru64 UNIX
Manufacturer Warranty	
Type	Limited warranty - parts - 3 years - response time: next day Technical support - phone consulting - 3 years - availability: 9 hours a day / Monday-Friday
Dimensions & Weight (Shipping)	
Shipping Width	31 cm
Shipping Depth	39 cm
Shipping Height	24 cm
Shipping Weight	2.3 kg
Environmental Parameters	
Min Operating Temperature	10 °C
Max Operating Temperature	35 °C
Humidity Range Operating	20 - 80% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.