

Yealink SIP-T54W - VoIP phone

with Bluetooth interface with caller ID - IEEE 802.11a/b/g/n/ac (Wi-Fi) - 3-way call capability - SIP - SIP v2 - SRTP - classic gray

Group	Phones
Manufacturer	Yealink
Manufacturer item no.	T54W
EAN/UPC	6938818303171



Description

The Yealink T5 business phones are for today's highly active voice communication users, providing them with advanced telephony features, HD communication experience and great flexibility.

Main features

Product Description	Yealink SIP-T54W - VoIP phone - with Bluetooth interface with caller ID - 3-way call capability
Product Type	VoIP phone - with Bluetooth interface with caller ID
Cordless Phone Standard	IEEE 802.11a/b/g/n/ac (Wi-Fi)
Main Features	Multiple VoIP protocol support, integrated Ethernet switch
VoIP Protocols	SIP, SIP v2, SRTP
Voice Codecs	G.722, G.723.1, G.726, iLBC, Opus, G.729A/B
Speakerphone	Yes
Call Services	Voice Mail, Caller ID, Call Waiting, Call Forwarding, Call Transfer, Call Hold
Display	LCD display - colour - Yes
Network Ports Qty	2 x Ethernet 10Base-T/100Base-TX/1000Base-T
Body Colour	Classic gray

Extended details

General

Product Type	VoIP phone
Integrated Components	Bluetooth interface
Body Colour	Classic gray

Phone Features

Operating System	Linux
Cordless Phone Standard	IEEE 802.11a/b/g/n/ac (Wi-Fi)
Wireless Interface Provided	Wi-Fi / Bluetooth
Call Services	Voice Mail, Caller ID, Call Waiting, Call Forwarding, Call Transfer, Call Hold

Caller ID Type	Caller ID
Dialer Location	Base
Conference Call Capability	3-way
Speakerphone	Yes
Messaging Services	SMS
Programmable Buttons Qty	10
Volume Control	Yes
Indicators	Voice message waiting indicator
Additional Functions	Call recording, redial, mute, call park, Optimal HD Voice, call pickup
IP Telephony	
Main Features	Multiple VoIP protocol support, integrated Ethernet switch
VoIP	Yes
VoIP Protocols	SIP, SIP v2, SRTP
Voice Codecs	G.722, G.723.1, G.726, iLBC, Opus, G.729A/B
Quality of Service	IEEE 802.1Q (VLAN), IEEE 802.1p, Type of Service (ToS)
IP Address Assignment	DHCP, static, PPPoE
Security	IEEE 802.1X, TLS
Power Over Ethernet (PoE) Support	Yes
Network Protocols	TCP, TFTP, UDP, HTTP, DNS, HTTPS, SRTP, TR-069, SNTP
Network Ports Qty	2 x Ethernet 10Base-T/100Base-TX/1000Base-T
Voice Features	Comfort noise generation (CNG), voice activity detection (VAD), HD Voice, acoustic echo cancellation (AEC), packet loss concealment (PLC), adaptive jitter buffer (AJB), automatic gain control (AGC)
Network Features	Network Address Translation (NAT), Class 3 PoE, Lightweight Directory Access Protocol (LDAP)
Phone Memory	
Phone Directory Capacity	1000 names & numbers
Display	
Type	LCD display - colour
Display Location	Base
Diagonal Size	4.3"
Display Resolution	480 x 272 pixels
Backlit	Yes
Miscellaneous	
Connections	Headset jack / RJ-9 USB Handset jack / RJ-9
Hearing Aid Compatible	Yes
Placing / Mounting	Table-top
Cables Included	Network cable

Included Accessories	Stand
Dimensions & Weight (Base)	
Width	23.3 cm
Depth	22.26 cm
Height	18.61 cm

Technical data © 1WorldSync. Subject to technical modifications and errors.