

APC Smart-UPS X 1500 Rack/Tower LCD

UPS (rack-mountable) - AC 230 V - 1200 Watt - 1500 VA - RS-232 - USB - output connectors: 8 - 2U - black - for P/N: AR4018SPX432 - AR4024SP - AR4024SPX429 - AR4024SPX431 - AR4024SPX432 - NBWL0356A

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMX1500RMI2U
EAN/UPC	0731304268598



Description

Patent-pending operating mode that by passes unused electrical components in good power conditions to achieve very high operating efficiency without sacrificing any protection. Reduces or eliminates bulky transformers resulting in lighter units for ease of handling.

Main features

Product Description	APC Smart-UPS X 1500 Rack/Tower LCD - UPS - 1200 Watt - 1500 VA
Device Type	UPS - rack-mountable
Rack Size	2U
Weight	24.8 kg
Input Voltage	AC 230 V
Output Voltage	AC 230 V
Power Capacity	1200 Watt / 1500 VA
Input Connectors	Power IEC 60320 C14
Output connectors	8 x power IEC 60320 C13
Battery	Lead Acid
Battery Form Factor	Plug-in module
Batteries Qty	1
Run Time (Up To)	5.8 min at full load
Networking	RS-232, USB
Colour	Black
Dimensions (WxDxH)	8.9 cm x 49 cm x 43.2 cm
Designed For	P/N: AR2487G, AR3100W, AR3105SP, AR3105W, AR3140G, AR3140W, AR3150W, AR3155SP, AR3155W, AR3300W, AR3305W, AR3340G, AR3355SP, AR3355W, AR4018IX429, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4024IX431, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, NBWL0356A

Extended details

General

Device Type	UPS - rack-mountable
Battery Enclosure Type	Plug-in module
Height (Rack Units)	2U
Colour	Black
	Power Device
UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 160 - 285 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Provided	47 - 63 Hz
Frequency Required	50/60 Hz
Input Connectors	Power IEC 60320 C14
Power Output Connectors Details	8 x power IEC 60320 C13
Output Voltage	AC 230 V 47 - 63 Hz
Power Capacity	1200 Watt / 1500 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	645 Joules
	Battery
Quantity	1
Technology	Lead Acid
Run Time (Up To)	5.8 min at full load 17.2 min at half load
Recharge Time	3 hours
	Networking
Remote Management Interface	RS-232, USB
	Expansion / Connectivity
Interfaces	1 x management (RS-232) 1 x management (USB) 1 x EPO (emergency power off)
Expansion Slots	1 (total) / 1 (free) x SmartSlot
	Miscellaneous
Cables Included	Serial cable - external USB cable - external Power cable - integrated - 1.8 m
Rack Mounting Kit	Included
Features	Audible alarm, emergency power off, LCD display
Compliant Standards	C-Tick, UL 1449, VDE, EN 50091-2, RoHS Exemption 7b, EN 50091-1
	Software / System Requirements
Software Included	APC PowerChute Business Edition
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C

Max Operating Temperature	45 °C
Humidity Range Operating	0 - 95%
Sound Emission	40 dBA
Dimensions & Weight	
Width	8.9 cm
Depth	49 cm
Height	43.2 cm
Weight	24.8 kg
Dimensions & Weight (Shipping)	
Shipping Width	24.6 cm
Shipping Depth	62 cm
Shipping Height	58.9 cm
Shipping Weight	30 kg
Compatibility Information	
Designed For	P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF001, ACF002, ACF003, ACF101BLK, ACF102BLK, ACF201BLK, ACF400, ACF600, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR100, AR100HD, AR202, AR203A, AR204A, AR2101, AR2102BLK, AR2144BLK, AR2145BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X431, AR4038X432, AR7007, AR7050, AR7057, AR8135BLK, NBWL0356A

Technical data © 1WorldSync. Subject to technical modifications and errors.