

ZyXEL GS2220-50 - Switch - Managed

44 x 10/100/1000 + 4 x combo Gigabit SFP + 2 x Gigabit SFP - rack-mountable

Group	Network Equipment
Manufacturer	ZyXEL
Manufacturer item no.	GS2220-50-EU0101F
EAN/UPC	4718937607525



Description

Zyxel's GS2220 Series are fully featured Layer 2 Gigabit access switches designed to meet converged data, video and voice networking needs. On top of the fully manageable L2 features set comes with the state-of-the-art Zyxel NebulaFlex Pro technology for cloud manageability.

Main features

Product Description	ZyXel GS2220-50 - switch - 48 ports - Managed - rack-mountable
Device Type	Switch - 48 ports - Managed
Enclosure Type	Rack-mountable
Subtype	Gigabit Ethernet
Ports	44 x 10/100/1000 + 4 x combo Gigabit SFP + 2 x Gigabit SFP
Performance	Switching capacity: 100 Gbps Forwarding rate: 74 Mpps Packet buffer size: 1.5 MB
MAC Address Table Size	16K entries
Routing Protocol	IGMPv2, IGMP, IGMPv3, static IPv4 routing, static IPv6 routing, MLD, MSTP, RSTP, STP
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, TFTP, SSH-2, CLI, NTP, ICMP, DHCP, RSTP, TACACS+, RADIUS
Features	Flow control, IGMP snooping, Syslog support, port mirroring, IP address filtering, ZyXEL iStacking Technology, sFlow, Quality of Service (QoS), MLD snooping, LACP support, LLDP support, DHCP relay, Port Security, DHCP client, Management Information Base (MIB), Multicast VLAN Registration (MVR), port isolation, Class of Service (CoS), Generic VLAN Registration Protocol (GVRP), cloud managed, DiffServ Code Point (DSCP) support, ErrDisable Recovery, IP source guard, ARP inspection, dual image support, Root Guard, Loop Guard, LLDP-MED, Energy-Efficient Ethernet (EEE), VLAN Tagging, MRSTP
Compliant Standards	IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3az
Power	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH)	44 cm x 20 cm x 4.45 cm
Weight	2.9 kg
Localisation	Europe

Extended details

Device Type	Switch - 48 ports - Managed
Enclosure Type	Rack-mountable
Subtype	Gigabit Ethernet
Ports	44 x 10/100/1000 + 4 x combo Gigabit SFP + 2 x Gigabit SFP
Performance	Switching capacity: 100 Gbps Forwarding rate: 74 Mpps Packet buffer size: 1.5 MB
MAC Address Table Size	16K entries
Routing Protocol	IGMPv2, IGMP, IGMPv3, static IPv4 routing, static IPv6 routing, MLD, MSTP, RSTP, STP
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, TFTP, SSH-2, CLI, NTP, ICMP, DHCP, RSTP, TACACS+, RADIUS
Encryption Algorithm	SSL
Authentication Method	RADIUS, TACACS+, Secure Shell v.2 (SSH2)
Features	Flow control, IGMP snooping, Syslog support, port mirroring, IP address filtering, ZyXEL iStacking Technology, sFlow, Quality of Service (QoS), MLD snooping, LACP support, LLDP support, DHCP relay, Port Security, DHCP client, Management Information Base (MIB), Multicast VLAN Registration (MVR), port isolation, Class of Service (CoS), Generic VLAN Registration Protocol (GVRP), cloud managed, DiffServ Code Point (DSCP) support, ErrDisable Recovery, IP source guard, ARP inspection, dual image support, Root Guard, Loop Guard, LLDP-MED, Energy-Efficient Ethernet (EEE), VLAN Tagging, MRSTP
Compliant Standards	IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3az
RAM	256 MB
Flash Memory	32 MB
Status Indicators	Status
	Expansion / Connectivity
Interfaces	48 x 1000Base-T RJ-45 6 x 1000Base-X SFP 1 x serial (RS-232)
	Power
Power Device	Internal power supply
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	36.9 Watt
	Miscellaneous
Rack Mounting Kit	Included
MTBF	660,245 hours
Compliant Standards	BSMI, RoHS, FCC Part 15 A, LVD, EMC Class A
Localisation	Europe
	Dimensions & Weight
Width	44 cm
Depth	20 cm
Height	4.45 cm
Weight	2.9 kg
	Dimensions & Weight (Shipping)
Shipping Width	49.6 cm

Shipping Depth	28.9 cm
Shipping Height	9 cm
Shipping Weight	3.54 kg
Manufacturer Warranty	
Service & Support	Limited warranty - lifetime
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	50 °C
Humidity Range Operating	10 - 95%

Technical data © 1WorldSync. Subject to technical modifications and errors.