

Dell Networking Virtual Edge Platform 1405 VEP1445

Virtual network function (VNF) device - with 1 Year Parts Only Warranty - 10 GigE - Bluetooth - Wi-Fi 5 - 2.4 GHz - 5 GHz - rack-mountable

Group	Network Accessories
Manufacturer	Dell
Manufacturer item no.	210-ASHR
EAN/UPC	5397184224625



Description

Dell Networking Virtual Edge Platform 1405 VEP1445 - Virtual network function (VNF) device - with 1 Year Parts Only Warranty - 10 GigE - Bluetooth, Wi-Fi 5 - 2.4 GHz, 5 GHz - rack-mountable

Main features

Product Description	Dell Networking Virtual Edge Platform 1405 VEP1445 - virtual network function (VNF) device - Bluetooth, Wi-Fi 5 - with 1 Year Parts Only Warranty
Device Type	Virtual network function (VNF) device
Bundled Services	1 Year Parts Only Warranty
Form Factor	Rack-mountable
Processor	1 x Intel Atom C3758 - 2.2 GHz
RAM	16 GB
Flash Memory	16 GB
Hard Drive	240 GB x 1
Data Link Protocol	Gigabit Ethernet, Bluetooth, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, 10 Gigabit Ethernet, IEEE 802.11n, IEEE 802.11ac
Frequency Band	2.4 GHz, 5 GHz
Power	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH)	20.8 cm x 20 cm x 5.2 cm

Extended details

	General
Device Type	Virtual network function (VNF) device
Bundled Services	1 Year Parts Only Warranty
Width	20.8 cm
Depth	20 cm
Height	5.2 cm
	Processor / Memory / Storage

Processors Installed	1 x Intel Atom C3758 2.2 GHz
Max Supported Qty	1
RAM	16 GB DDR4 SDRAM DIMM 288-pin
Flash Memory	16 GB
Hard Drive	SSD 240 GB x 1 - M.2
Networking	
Form Factor	Rack-mountable
Connectivity Technology	Wireless, wired
Data Link Protocol	Gigabit Ethernet, Bluetooth, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, 10 Gigabit Ethernet, IEEE 802.11n, IEEE 802.11ac
Frequency Band	2.4 GHz, 5 GHz
Features	Wall mountable, Quality of Service (QoS), Multiple SSID support, built-in Intel QuickAssist crypto acceleration, 2x2 MIMO technology
Expansion / Connectivity	
Interfaces	6 x 1000Base-TX - RJ-45 2 x 10GBase-X - SFP+ 2 x USB 3.0 1 x console - micro-USB
Miscellaneous	
Compliant Standards	CISPR 22 Class A, CISPR 24, EN55024, EN50082-1, AS/NZS 60950-1, AS/NZ 3548 Class A, ICES-003 Class A, FCC CFR47 Part 15, UL 60950-1, IEC 60950-1, EN 60950-1, GB 4943, VCCI V-3, EN 61000, CNS 13438, EN 55022 Class A, EN 300 386, CAN/CSA-C22.2 No. 60950-1
Power	
Power Device	External power adapter
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	35 Watt
Dimensions & Weight (Shipping)	
Shipping Width	49.5 cm
Shipping Depth	28.7 cm
Shipping Height	10.9 cm
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	5 - 85%

Technical data © 1WorldSync. Subject to technical modifications and errors.