

# Epson EB-PU1008B - 3LCD projector

8500 lumens (white) - 8500 lumens (colour) - WUXGA (1920 x 1200) - 16:10 - 1080p - LAN - black

Group	Projectors
Manufacturer	Epson
Manufacturer item no.	V11HA33840
EAN/UPC	8715946697277



## Description

The EB-PU1008B offers larger-than-life images from a sleek, powerful projector that's easy to install. The most compact within Epson's Pro Series, it's compatible with a wide range of optional powered lenses, including a zero offset, .35 ultra-short-throw lens.

Delivering best-in-class color brightness, with 8,500 lumens of color brightness and 8,500 lumens of white brightness, this 3-chip, 3LCD projector features a virtually maintenance-free 20,000 hour laser light source and air filter.

Full HD WUXGA resolution and 4K Enhancement Technology (1920 x 1200 x 2) mean you get crystal-clear, lifelike images. Built-in NFC function reduces the time to install and commission multiple projectors. And a clip-on optional external camera allows access to powerful automated tools including auto color calibration, screen matching of multiple projectors, tiling assist for edge blends, and the stacking assist function.

## Main features

Product Description	Epson EB-PU1008B - 3LCD projector - LAN - black
Device Type	3LCD projector - 1080p
Colour	Black
Built-in Devices	0.76-inch LCD
Brightness (White)	8500 lumens
Brightness (Colour)	8500 lumens
Contrast Ratio	2000:1 / 2500000:1 (dynamic)
Resolution	WUXGA (1920 x 1200)
Native Aspect Ratio	16:10
Colour Support	1.07 billion colours
Bulb type	Laser
Bulb life cycle	Up to 20000 hour(s) - normal mode   Up to 30000 hour(s) - economic mode
Video Input	LAN
Power	AC 120/230 V (50 - 60 Hz)
Power Consumption Operational	535 Watt

Dimensions (WxDxH)	54.5 cm x 43.6 cm x 18.9 cm
Weight	16.3 kg

Extended details

	<b>General</b>
Device Type	3LCD projector - 1080p
Built-in Devices	0.76-inch LCD
Networking	Ethernet
Enclosure Colour	Black
	<b>Projector</b>
Brightness (White)	8500 lumens
Brightness (Colour)	8500 lumens
Brightness (Reduced)	5950 lumens
Contrast Ratio	2000:1 / 2500000:1 (dynamic)
Throw Ratio	0.35 - 10.11:1
Resolution	WUXGA - WUXGA (1920 x 1200)
Native Aspect Ratio	16:10
Colour Support	1.07 billion colours
Bulb type	Laser
Bulb life cycle	Up to 20000 hour(s) - normal mode   Up to 30000 hour(s) - economic mode
Features	EPSON Quick Corner, Edge blending, EPSON 3LCD technology, PJlink, Web Remote Control, DICOM Simulation Mode, AMX Device Discovery, Direct Power On, Direct Power Off, Dynamic Mode, full 10-bit image processing, auto power on, SNMP support, Extron XTP certified, 4K Enhancement, Presentation Mode, Extron IPLink certified, Cinema Mode, RGB liquid crystal shutter
	<b>Lens</b>
Keystone Correction Direction	Horizontal, vertical
Vertical Keystone Correction	-45 / +45
Horizontal Keystone Correction	-30 / +30
	<b>Video Input</b>
Video Interfaces	VGA, HDMI, DVI, HDBaseT
LAN and Wireless Image Transferring Protocols	Wired LAN

<b>Expansion / Connectivity</b>	
Interfaces	2 x USB 2.0 - 4 pin USB Type A   1 x USB 2.0 - 4 pin USB Type B (management)   1 x serial RS-232C   1 x network - RJ-45   1 x VGA input - 15 pin HD D-Sub (HD-15)   1 x DVI input   1 x HDBaseT - RJ-45   1 x audio line-out - mini-phone stereo 3.5 mm   HDMI - 19 pin HDMI Type A
<b>Miscellaneous</b>	
Included Accessories	Cable cover, remote control, battery for remote control
Security Features	Security lock slot (cable lock sold separately), password protection, control panel lock, Wireless LAN Lock, padlock, security cable hole
Security Slot Type	Kensington security slot
Compliant Standards	HDCP 2.3, IPv6
<b>Power</b>	
Power Source	AC
Voltage Required	AC 120/230 V (50 - 60 Hz)
Power Consumption Operational	535 Watt
Power Consumption Stand by	0.5 Watt
<b>Software / System Requirements</b>	
Software Included	Epson Projector Management Software, Epson iProjection, Epson Projector Content Manager, Epson Projector Professional Tool
<b>Dimensions &amp; Weight</b>	
Width	54.5 cm
Depth	43.6 cm
Height	18.9 cm
Weight	16.3 kg
<b>Manufacturer Warranty</b>	
Service & Support	Limited warranty - 3 years - carry-in
<b>Environmental Parameters</b>	
Humidity Range Operating	20 - 80%
Sound Emission	35 dBA
Sound Emission (Economic Mode)	30 dBA

Technical data © 1WorldSync. Subject to technical modifications and errors.