

Raritan PX3-4516-M11, Managed, Metered, Monitored, 0U, Three-phase, Vertical, Black, LCD

11.5kVA - 21xC13 - 3xC19 - 220-240V - 1298x65x52mm

Group	Power Supply
Manufacturer	Raritan
Manufacturer item no.	PX3-4516-M11



Description

Raritan PX3-4516-M11. PDU types: Managed, Metered, Monitored, Rack capacity: 0U, Type: Three-phase. AC outlets quantity: 24 AC outlet(s), AC outlet types: C13 coupler, C19 coupler, Power plug: IEC 60309. Cable length: 3 m, Certification: CE, Canada ICES-003, Part 15 Class A of the FCC. Monitoring: Current, Humidity, Temperature, Management protocols: HTTP(s); SSH; Telnet; RS-232 (Serial); Power IQ; SNMP version v2/v3; SMTP; JSON-RPC; Modbus over.... Nominal input voltage: 380-415 V, Maximum current: 16 A, AC input frequency: 50/60 Hz

Main features

	General
PDU types	Managed, Metered, Monitored
Rack capacity	0U
Type	Three-phase
AC outlets quantity	24 AC outlet(s)
AC outlet types	C13 coupler, C19 coupler
Power plug	IEC 60309
Cable length	3 m
Certification	CE, Canada ICES-003, Part 15 Class A of the FCC
Monitoring	Current, Humidity, Temperature
Management protocols	HTTP(s); SSH; Telnet; RS-232 (Serial); Power IQ; SNMP version v2/v3; SMTP; JSON-RPC; Modbus over TCP
Nominal input voltage	380-415 V
Maximum current	16 A
AC input frequency	50/60 Hz