

Advantech DLoG DLT-V7210 K - Rugged

vehicle mount computer - Intel Atom E3845 / 1.91 GHz - Win 10 IoT Enterprise - 4 GB RAM - 64 GB - 10.1" touchscreen 1280 x 800 - kbd: US/Europe

Group	Input Devices
Manufacturer	Advantech
Manufacturer item no.	D-V7210CA12Y5H9AA0



Description

DLT-V7210 K series is a rugged vehicle-mounted terminal with integrated keyboard designed for logistics applications and to provide maximum system uptime. DLT-V7210 KD also offers PCT defroster, which is ideal for cold chain and cold storage applications. The low-profile antenna offers excellent transmission capabilities in a compact form factor. Furthermore, the integrated user-friendly keyboard offers convenient operation and efficient data input. Meanwhile, the 10.1" widescreen WXGA color TFT display with touch control allows easy input and configurable touch sensitivity ensures easy operation with gloves.

Main features

Product Description	Advantech DLoG DLT-V7210 K - 10.1" - Atom E3845 - 4 GB RAM - 64 GB - US/Europe
Product Type	Vehicle mount computer - rugged
Operating System	Win 10 IoT Enterprise
Processor	Intel Atom E3845 / 1.91 GHz
Memory	4 GB
Storage	64 GB
Display	10.1" touchscreen 1280 x 800 / WXGA
Input Device	12 x control buttons, 55 keys keyboard
Keyboard	US/Europe
Networking	802.11a/b/g/n, Gigabit Ethernet
Features	Accelerometer
Dimensions (WxDxH) - tablet	29.73 cm x 26.47 cm x 8 cm
Weight	3.7 kg
Localisation	Region: United States, Europe

Extended details

	General
Product Type	Vehicle mount computer - rugged
Operating System	Windows 10 IoT Enterprise
	Processor / Chipset
CPU	Intel Atom E3845 / 1.91 GHz

Number of Cores	Quad-Core
Memory	
RAM	4 GB
Storage	
Main Storage	64 GB
Display	
Type	10.1"
Touchscreen	Yes (multi-touch)
Resolution	1280 x 800 (WXGA)
Widescreen	Yes
Image Brightness	500 cd/m²
Audio & Video	
Sound	Speaker
Input	
Type	12 x control buttons, 55 keys keyboard
Keyboard Layout	US/Europe
Features	6 programmable buttons
Communications	
Wireless	802.11a/b/g/n
Network Interface	Gigabit Ethernet
Connections & Expansion	
Interfaces	4 x USB 2.0 2 x serial (RS-232) LAN USB 3.0
Miscellaneous	
Case Material	Aluminum
Integrated Options	Accelerometer
Features	Fanless
Compliant Standards	MIL-STD 810F, FCC Class B certified, CCC, IP65, IEC 60721-3-5, EN 62262 IK08
Localization	Region: United States, Europe
Dimensions & Weight	
Dimensions (WxDxH) - tablet	29.73 cm x 26.47 cm x 8 cm
Weight	3.7 kg
Environmental Parameters	
Min Operating Temperature	-30 °C
Max Operating Temperature	50 °C
Humidity Range Operating	10 - 95% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.