

ZyXEL GS-105S v2 - Switch - unmanaged

5 x 10/100/1000 - desktop

Group	Network Equipment
Manufacturer	ZyXEL
Manufacturer item no.	GS-105SV2-EU0101F
EAN/UPC	4718937578757



Description

The ZyXEL GS-105S v2 5-Port Desktop Gigabit Ethernet Media Switch can easily connect multiple media devices to home networks at blazing-fast Gigabit simultaneously. Moreover, the newly designed GS-105S v2 allow smooth video streaming and online gaming activities.

Main features

Product Description	Zyxel GS-105S v2 - switch - 5 ports - unmanaged
Device Type	Switch - 5 ports - unmanaged
Subtype	Gigabit Ethernet
Ports	5 x 10/100/1000
Performance	Switching fabric bandwidth: 10 Gbps
MAC Address Table Size	2K entries
Jumbo Frame Support	9KB
Routing Protocol	IGMPv2, IGMP
Features	Flow control, auto-negotiation, auto-uplink (auto MDI/MDI-X), IGMP snooping, store and forward, half duplex mode, full duplex mode, Quality of Service (QoS), 128KB packet buffer, Energy Efficient Ethernet
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.3az
Power	AC 120/230 V 1 A
Dimensions (WxDxH)	10.6 cm x 7.5 cm x 3.2 cm
Weight	105 g
Localisation	Europe

Extended details

General	
Device Type	Switch - 5 ports - unmanaged
Enclosure Type	Desktop
Subtype	Gigabit Ethernet
Ports	5 x 10/100/1000
Performance	Switching fabric bandwidth: 10 Gbps
MAC Address Table Size	2K entries

Jumbo Frame Support	9KB
Routing Protocol	IGMPv2, IGMP
Features	Flow control, auto-negotiation, auto-uplink (auto MDI/MDI-X), IGMP snooping, store and forward, half duplex mode, full duplex mode, Quality of Service (QoS), 128KB packet buffer, Energy Efficient Ethernet
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.3az
Status Indicators	Power, link/activity
Expansion / Connectivity	
Interfaces	1 x 1000Base-T RJ-45 high priority 2 x 1000Base-T RJ-45 medium priority 2 x 1000Base-T RJ-45 low priority
Power	
Power Device	External power adapter
Voltage Required	AC 120/230 V
Electric Current Required	1 A
Power Consumption Operational	2.5 Watt
Miscellaneous	
Compliant Standards	Plug and Play, FCC Class B certified, BSMI
Localisation	Europe
Dimensions & Weight	
Width	10.6 cm
Depth	7.5 cm
Height	3.2 cm
Weight	105 g
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)
Min Storage Temperature	-20 °C
Max Storage Temperature	70 °C
Humidity Range Storage	10 - 90% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.