Axis FA51 Main Unit - Video server

1 channels

Group	Network Cameras
Manufacturer	Axis
Manufacturer item no.	02196-021
EAN/UPC	7331021074552

Description

AXIS FA51 Main Unit - Video server - 1 channels

Main features

Product Description	AXIS FA51 Main Unit - video server - 1 channels
Device Type	Video server - 1 channels
Compression Format	MPEG-4, H.264, AVC, Motion JPEG
Voltage	12 V
Dimensions (WxDxH)	4.9 cm x 15.2 cm x 2.4 cm
Weight	195 g

Extended details

	General
Device Type	Video server
Video Channels	1
Compression Format	MPEG-4, H.264, AVC, Motion JPEG
Package Content	Terminal block
Software Included (Y)	Windows decoder 1-user licence, AXIS Face Detector, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, AXIS Video Motion Detection, AXIS People Counter
Compliant Standards	EN 61000-6-1, EN 61000-6-2, IEC 60068-2-27, IEC 60068-2-6, FCC Part 15 B Class A, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, VCCI Class A, RCM, IS13252, KN35, AS/NZS CISPR 32 Class A, KN32 Class A, BFR-free, EN 55032 Class A, IEEE 802.3af, CAN/CSA-C22.2 No. 62368-1, EN 55035, IEC/EN/UL 62368-1, IEEE 802.1x, PVC-free, NIST SP500-267, ICES-3(A)/NMB-3(A), CFR free, IEC/EN 60529 IP4X
Colour	Black
	Video Server
RAM	1 GB
Flash Memory	512 MB
Features	microSD/SDHC/SDXC memory card slot, Forensic WDR, Zipstream
	Networking

Network Interfaces	Ethernet 10Base-T/100Base-TX
Supported Protocols	DDNS, DHCP, DNS, FTP, HTTP, NTP, SMTP, TCP/IP, ICMP, SNMP 1, SNMP 2c, SNMP 3, SOCKS, RTSP, RTP, HTTPS, UPnP, TLS, IPv4, IPv6, Bonjour, RTCP, SMB, SSH, QOS, CIFS, SRTP, SFTP, Zeroconf, USGv6, MQTT, CDP, Syslog
Features	Modular design, DiffServ support, IP address filtering, HDTV Compatible, 1080p resolution support, active anti tampering system, secure boot, HTTPS encryption, PoE powered, Variable Bit Rate (VBR), aluminium housing, Brute Force Protection, password protection, digest authentication, signed firmware, Adaptive Bit Rate (ABR), Multi-Bit Rate (MBR), digital PTZ, network access control, multi-level user, signed video, Axis Edge Vault, Axis device ID, secure keystore, ONVIF Profile M, ONVIF Profile S, ONVIF Profile T, ONVIF Profile G, autotracking
	Connections
Video Output Ports	HDMI x 1
Audio Input Ports	Terminal block
Audio Output Ports	Terminal block
Network Port	10/100Base-T
Other Ports	RJ-45, RJ-12 x 1
	Power
Voltage	12 V
Power Consumption	5.2 Watt
	Dimensions & Weight
Width	4.9 cm
Depth	15.2 cm
Height	2.4 cm
Weight	195 g
	Environmental Parameters
Min Operating Temperature	-20 °C
Max Operating Temperature	50 °C
Humidity Range Operating	10 - 85% RH (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.