

Poly Studio X30 - Video conferencing device

Zoom Certified

Group	Network Cameras
Manufacturer	Poly
Manufacturer item no.	2200-85980-101
EAN/UPC	0610807895107



Description

Poly Studio X30 Video Bar delivers radical simplicity in a small and elegant package. Now you can huddle happy in smaller rooms and connect easy in conference rooms with whatever video collaboration software you use, including native Zoom Rooms. Experience full board-room quality audio, advanced camera capabilities, and wireless content sharing that you can fling your content onto in seconds, all miniaturized into one sleek bar. So, say good bye to pucks, cords, and cables. Ditch the PC to drive the meeting, since the Poly Video OS runs the show. Easy to install, easy to manage - and best of all, easy to use. The new Poly Studio X line of video bars puts the mojo back into meetings.

Main features

Product Description	Poly Studio X30 - video conferencing device
Device Type	Video conferencing device
VoIP Protocols	H.323, SIP
Codec	H.264, H.265, H.264 High Profile, G.711, G.722, G.728, G.729a, G.722.1, G.722.1c, AAC-LD, G.719
Dimensions (WxDxH)	44.18 cm x 6.16 cm x 6.25 cm
Weight	730 g
Localisation	Europe
Video Input	Digital camera - HDMI input
Video Output	3840 x 2160
Audio Input	Four microphones
Audio Output	Speaker(s) - mono
Networking	Network adapter - Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, Bluetooth 5.0
Power	AC 120/230 V (50/60 Hz)
Software Certification	Zoom Certified

Extended details

General	
Device Type	Video conferencing device
VoIP Protocols	H.323, SIP
Voice Codecs	G.711, G.722, G.728, G.729a, G.722.1, G.722.1c, AAC-LD, G.719

Video Codecs	H.264, H.265, H.264 High Profile
Security	128 bit AES, 256 bit AES, H.235.6
Network Features	Authenticated access to admin menus, web interface, and APIs, local account password policy configuration, security profiles, local account and login port lockout, secure defaults, remote logging with support for TLS, active directory external authentication
Width	44.18 cm
Depth	6.16 cm
Height	6.25 cm
Weight	730 g
Built-in Devices	Speaker, camera, 4 microphones
Localisation	Europe
	Video Input
Type	Digital camera - integrated
Interface Type	HDMI input
Digital Video Capture Resolution	1280 x 720, 1024 x 768, 1280 x 1024, 1920 x 1080, 3840 x 2160, 1920 x 1200, 1680 x 1050, 1400 x 1050
Video Modes	720/60p, 1080/60p, 1080/30p, 720/30p, 4K
Digital Zoom	4
Features	Interactive whiteboard compatibility, 120° field of view, automatic speaker tracking, automatic group framing, Poly content sharing, content annotation, UHD 2160p (4K) capture resolution
	Video Output
Max External Resolution	3840 x 2160
Supported Display Graphics	XGA (1024x768), SXGA (1280x1024), SXGA+ (1400x1050), HDTV (1920x1080), WUXGA (1920 x 1200), HD (1280 x 720), WSXGA+ (1680 x 1050), UHD (3840 x 2160)
Digital Video Standard	High-Definition Multimedia Interface (HDMI)
	Audio Input
Type	Four microphones
	Audio Output
Type	Speaker(s)
Sound Output Mode	Mono
	Networking
Type	Network adapter
Connectivity Technology	Wireless, wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, Bluetooth 5.0
Features	OCSP support, auto-uplink (auto MDI/MDI-X), MIMO technology, IPv4 support, Wi-Fi Miracast ready, Apple AirPlay, Polycom Lost Packet Recovery (LPR) technology, Simple Certificate Enrollment Protocol (SCEP)
Compliant Standards	IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, Bluetooth 5.0
	Expansion / Connectivity

Interfaces	1 x audio / video - HDMI input - 19 pin HDMI Type A 1 x audio / video - HDMI output - 19 pin HDMI Type A 1 x SuperSpeed USB 3.0 1 x USB-C - 24 pin USB-C 1 x network - Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45
	Miscellaneous
Included Accessories	Clamp, cables
Software Certification	Zoom Certified
Compliant Standards	FIPS 140-2
	Power
Power Device	Power adapter - external
Voltage Required	AC 120/230 V (50/60 Hz)
	Manufacturer Warranty
Service & Support	Limited warranty - parts and labour - 1 year
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	5 - 90% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.