

Datalogic PowerScan PBT9501-AR

USB Kit - barcode scanner - handheld - 2D imager - decoded - Bluetooth 3.0

Group	Scanners
Manufacturer	Datalogic
Manufacturer item no.	PBT9501-ARRBK10EU



Description

The PowerScan retail series is for users who want to incorporate the durability of PowerScan imagers into a retail environment. Repeated shocks at the POS checkout or outdoor usage do not inhibit the scanner's performance or reliability, protecting the retailer's investment.

Main features

Product Description	Datalogic PowerScan PBT9501-AR - USB Kit - barcode scanner
Type	Barcode scanner - handheld - Bluetooth 3.0 - decoded
Colour	Black, yellow
Localisation	European Union
Minimum Bar Width	3 mil
Scan Element Type	2D imager
Connectivity Technology	Wireless
Wireless Connectivity	Bluetooth 3.0
Battery	1 x Lithium Ion
Dimensions (WxDxH)	7.4 cm x 11 cm x 21.2 cm
Weight	460 g

Extended details

	General
Type	Barcode scanner - handheld
Colour	Black, yellow
Localisation	European Union
	Barcode
Interface Type	Bluetooth 3.0
Minimum Bar Width	3 mil
Scan Element Type	2D imager
Scan Mode	Single-pass
Max Working Distance	20 m
Skew (Degrees)	60

Pitch (Degrees)	80
Print Contrast Signal (PCS)	15%
Decode Capability	EAN/JAN, GS1 DataBar, QR code, MaxiCode, Aztec code, MicroPDF417, Postnet, PDF417, Data Matrix, PLANET, Australian Post, China Post, Japanese Post, Kix (Netherlands) Post, MacroPDF417, Royal Mail, Micro QR code, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, Swedish Post, GS1 DataBar Composites, GS1 DataBar Stacked, China Han Xin Code, Portuguese Post, Intelligent Mail Barcode, UPC-A / E
TTL Decoding	Decoded
Connectivity Technology	Wireless
OK Notification	Beeper, LED indicator
Features	Waterproof, rugged, Datalogic Three Green Lights (3GL), autofocus, removable battery, Human Interface Device Profile (HID), Serial Port Profile (SPP), drop protection, 20 kV ESD protection (air discharge)
	Networking
Wireless Connectivity	Bluetooth 3.0
	Miscellaneous
Included Accessories	Cradle
Compliant Standards	Bluetooth Class 1, IP65, EN 60825-1 Class 2, CDRH Class II, China RoHS, EU RoHS, IEC/EN/UL 62471
	Power
Power Device	Power adapter
Battery	1 x Lithium Ion
	Software
Software Included	Datalogic Aladdin, OPOS/JavaPOS Drivers
	Dimensions & Weight
Width	7.4 cm
Depth	11 cm
Height	21.2 cm
Weight	460 g
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years
	Environmental Parameters
Min Operating Temperature	-20 °C
Max Operating Temperature	50 °C
Humidity Range Operating	0 - 95% (non-condensing)
Drop Specification	2 m to concrete

Technical data © 1WorldSync. Subject to technical modifications and errors.