

APC Replacement Battery Cartridge #23

UPS battery - Lead Acid - black - for P/N: SUA1000R21CH - SUA1000RM2UTW - SUA1000RMI2U(P) - SUA1000RMI2U-3XW - SUA1000RMI2U-5XW

Group	Batteries
Manufacturer	APC
Manufacturer item no.	RBC23
EAN/UPC	0731304015789



Description

In the E-world where businesses can't stop and downtime is measured in dollars, American Power Conversion (APC) provides protection against some of the leading causes of downtime, data loss and hardware damage: power problems and temperature. As a global leader in power availability solutions, APC sets the standard in its industry for quality, innovation and support. Its comprehensive power solutions, which are designed for both home and corporate environments, improve the manageability, availability and performance of sensitive electronic, network, communications and industrial equipment of all sizes.

Main features

Product Description	APC Replacement Battery Cartridge #23 - UPS battery - Lead Acid
Device Type	UPS battery
Weight	10 kg
Battery	Lead Acid
Battery Form Factor	Plug-in module
Colour	Black
Dimensions (WxDxH)	21.6 cm x 34.3 cm x 8.3 cm
Designed For	P/N: SU1000R2BX120, SU1000R2IBX120, SU1000RMI2U, SUA1000R21CH, SUA1000RM2U, SUA1000RM2U-TU, SUA1000RM2UTW, SUA1000RMI2U, SUA1000RMI2U(P), SUA1000RMI2U-1EW, SUA1000RMI2U-2EW, SUA1000RMI2U-3EW, SUA1000RMI2U-3XW, SUA1000RMI2U-5XW, SUA1000RMI2U-BRZ, SUA1000RMI2U-GLD, SUA1000RMI2U-SLV, SUA1000RMUS

Extended details

General	
Device Type	UPS battery
Battery Enclosure Type	Plug-in module
Colour	Black
Battery	
Technology	Lead Acid
Features	Spill-proof
Manufacturer Warranty	
Service & Support	Limited warranty - 2 years

Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	45 °C
Min Storage Temperature	-15 °C
Max Storage Temperature	45 °C
Humidity Range Operating	0 - 95%
Dimensions & Weight	
Width	21.6 cm
Depth	34.3 cm
Height	8.3 cm
Weight	10 kg
Dimensions & Weight (Shipping)	
Shipping Width	36.8 cm
Shipping Depth	49.5 cm
Shipping Height	15.2 cm
Shipping Weight	10.9 kg
Compatibility Information	
Designed For	P/N: SU1000R2BX120, SU1000R2IBX120, SU1000RM2U, SU1000RMI2U, SUA1000R2ICH, SUA1000RM2U, SUA1000RM2U-TU, SUA1000RM2UTW, SUA1000RMI2U, SUA1000RMI2U(P), SUA1000RMI2U-1EW, SUA1000RMI2U-2EW, SUA1000RMI2U-3EW, SUA1000RMI2U-3XW, SUA1000RMI2U-5XW, SUA1000RMI2U-BRZ, SUA1000RMI2U-GLD, SUA1000RMI2U-SLV, SUA1000RMUS

Technical data © 1WorldSync. Subject to technical modifications and errors.