

APC Back-UPS CS 350 - UPS - AC 230 V

210 Watt - 350 VA - RS-232 - USB - output connectors: 4 - beige

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	BK350EI
EAN/UPC	0731304016342



Description

The Back-UPS CS offers best value for protecting your business and office computer systems. It provides battery backup power that allows you to work through short and medium length power outages. It also safeguards your equipment from damaging surges and spikes. Additional features like audible alarms, LED status indicators, user replaceable battery, push-button circuit breakers and transformer-block spaced outlets make the Back-UPS CS the perfect unit to protect your business' productivity from the constant threat of power outages and lost data.

Main features

Product Description	APC Back-UPS CS 350 - UPS - 210 Watt - 350 VA
Device Type	UPS - external
Weight	6.3 kg
Load Rating	Individual PC
Input Voltage	AC 230 V
Output Voltage	AC 230 V
Power Capacity	210 Watt / 350 VA
Input Connectors	1 x power IEC 60320 C14
Output connectors	1 x power IEC 60320 C13 (surge) 3 x power IEC 60320 C13 (UPS and surge)
Battery	Lead Acid
Battery Form Factor	Plug-in module
Batteries Qty	1
Run Time (Up To)	4.7 min at full load
Networking	RS-232, USB
Colour	Beige
Dimensions (WxDxH)	9.1 cm x 28.4 cm x 16.5 cm

Extended details

General	
Device Type	UPS - external
Battery Enclosure Type	Plug-in module
Colour	Beige

	Power Device
Load Rating	Individual PC
Supported Battery Technology	Lead Acid
Input Voltage	AC 230 V
Input Voltage Range	AC 196 - 280 V
Frequency Required	50/60 Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	1 x power IEC 60320 C13 (surge) 3 x power IEC 60320 C13 (UPS and surge)
Output Voltage	AC 230 V
Power Capacity	210 Watt / 350 VA
Dataline Surge Protection	Phone line - RJ-45
Surge Suppression	Yes
Surge Energy Rating	300 Joules
Circuit Protection	Circuit breaker
	Battery
Quantity	1
Technology	Lead Acid
Run Time (Up To)	4.7 min at full load
Recharge Time	6 hours
	Networking
Remote Management Interface	RS-232, USB
	Expansion / Connectivity
Interfaces	1 x USB / serial RS-232 - RJ-45
	Miscellaneous
Cables Included	USB cable - external
Features	Audible alarm
Compliant Standards	C-Tick, GOST, UL 1449, VDE, EN 50091-2, EN 50091-1
	Software / System Requirements
Software Included	APC PowerChute Personal Edition
	Manufacturer Warranty
Service & Support	Limited warranty - replace or repair - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Min Storage Temperature	-15 °C
Max Storage Temperature	45 °C
Humidity Range Operating	0 - 95%
Humidity Range Storage	0 - 95%

Sound Emission	40 dBA
Dimensions & Weight	
Width	9.1 cm
Depth	28.4 cm
Height	16.5 cm
Weight	6.3 kg
Dimensions & Weight (Shipping)	
Shipping Width	24.1 cm
Shipping Depth	36.8 cm
Shipping Height	17.8 cm
Shipping Weight	7.1 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.