

APC Replacement Battery Cartridge #12

UPS battery - 2 x battery - Lead Acid - black - for P/N: DL5000RMT5U
 - SU3000R3IX160 - SU5000R5TBX114 - SU5000R5TBXFMR -
 SU5000R5XLT-TF3

Group	Batteries
Manufacturer	APC
Manufacturer item no.	RBC12
EAN/UPC	0731304003342



Description

In the E-world where businesses can't stop and downtime is measured in dollars, American Power Conversion (APC) provides protection against some of the leading causes of downtime, data loss and hardware damage: power problems and temperature. As a global leader in power availability solutions, APC sets the standard in its industry for quality, innovation and support. Its comprehensive power solutions, which are designed for both home and corporate environments, improve the manageability, availability and performance of sensitive electronic, network, communications and industrial equipment of all sizes.

Main features

Product Description	APC Replacement Battery Cartridge #12 - UPS battery - Lead Acid
Device Type	UPS battery
Weight	10 kg
Battery	Lead Acid
Battery Form Factor	Internal
Batteries Qty	2
Colour	Black
Dimensions (WxDxH)	25.4 cm x 15.2 cm x 9.7 cm
Designed For	P/N: DL5000RMT5U, IAX1SU3KP1, PSXBRSU5KT, SU2200R3X147, SU2200RMUS, SU3000R3BX135, SU3000R3IX160, SU3000R3X145, SU3000RMUS, SU5000R5TBX114, SU5000R5TBX120, SU5000R5TBX135, SU5000R5TBXFMR, SU5000R5T-TF3, SU5000R5XLT-TF3, SU5000R5XLTXFMR, SU5000RMT5UXFMR, SU5000RMXLI5U, SU5000RMXLT5U, SU5000TX168

Extended details

General	
Device Type	UPS battery
Battery Enclosure Type	Internal
Colour	Black
Battery	
Quantity	2

Technology	Lead Acid
Features	Maintenance free, sealed, leak-proof
	Miscellaneous
Compliant Standards	RoHS, REACH
	Manufacturer Warranty
Service & Support	Limited warranty - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Min Storage Temperature	-15 °C
Max Storage Temperature	45 °C
Humidity Range Operating	0 - 95%
Humidity Range Storage	0 - 95%
	Dimensions & Weight
Width	25.4 cm
Depth	15.2 cm
Height	9.7 cm
Weight	10 kg
	Dimensions & Weight (Shipping)
Shipping Width	39.4 cm
Shipping Depth	57.2 cm
Shipping Height	22.9 cm
Shipping Weight	22.86 kg
	Compatibility Information
Designed For	P/N: DL5000RMT5U, IAX1SU3KP1, PSXBRSU5KT, SU1400RMXLNET, SU2200R3BX120, SU2200R3IBX120, SU2200R3X106, SU2200R3X147, SU2200R3X152, SU2200R3X167, SU2200RM3U, SU2200RMI3U, SU2200RMUS, SU3000R3BX120, SU3000R3BX135, SU3000R3IBX120, SU3000R3IX160, SU3000R3X145, SU3000RM3U, SU3000RMI3U, SU3000RMT3U, SU3000RMTX136, SU3000RMUS, SU5000I, SU5000R5IBX120, SU5000R5TBX114, SU5000R5TBX120, SU5000R5TBX135, SU5000R5TBXFMR, SU5000R5T-TF3, SU5000R5XLT-TF3, SU5000R5XLTXFMR, SU5000RMI5U, SU5000RMT5U, SU5000RMT5UXFMR, SU5000RMXLI5U, SU5000RMXLT5U, SU5000T, SU5000TX168, SU5000TXFMR

Technical data © 1WorldSync. Subject to technical modifications and errors.