

HP P34hc G4 - P-Series - LED monitor

curved - 34" - 3440 x 1440 WQHD @ 60 Hz - VA - 250 cd/m² - 3500:1 - 5 ms - HDMI - DisplayPort - USB-C - speakers - black

Group	Flat Screens
Manufacturer	HP
Manufacturer item no.	21Y56AA#ABB
EAN/UPC	0195122737191



Description

When it comes to the P34hc WQHD curved monitor, bigger really is better. Because its immersive, ultrawide screen keeps you focused, you're likely to be less distracted and up to 33% more productive compared to a smaller screen.

Main features

Product Description	HP P34hc G4 - P-Series - LED monitor - curved - 34"
Device Type	LED-backlit LCD monitor - 34"
Energy Class	Class G
Power Consumption (On mode)	34 W
Curved Screen	Yes
Features	USB 3.2 Gen 1 hub, USB PD 65 Watt
Panel Type	VA
Aspect Ratio	21:9
Native Resolution	WQHD 3440 x 1440 at 60 Hz
Pixel Pitch	0.23175 mm
Brightness	250 cd/m ²
Contrast Ratio	3500:1 / 50000000:1 (dynamic)
Response Time	5 ms (grey-to-grey with overdrive)
Colour Gamut	85% NTSC
Input Connectors	HDMI, DisplayPort, USB-C
Display Position Adjustments	Height, tilt
Screen Coating	Anti-glare, 3H Hard Coating, Haze 25%
Voltage	AC 120/230 V (50/60 Hz)
Colour	Black
Dimensions (WxDxH) - with stand	80.94 cm x 23.49 cm x 51.8 cm
Weight	10.51 kg
Localisation	English / Europe

Environmental Standards	TCO Certified Displays 8, TCO Certified Edge Displays, ENERGY STAR Qualified
Compliant Standards	TUV, VCCI, GS, NOM, WHQL, CB, CCC, FCC, ISO 9241-307, KCC, WEEE, cTUVus, KC, CEL, EPA, EAC, RCM, BIS, low halogen, DisplayPort 1.2, ICE, KES

Extended details

	General
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class G
Diagonal Size	34"
Curved Screen	Yes (1500R)
Built-in Devices	USB 3.2 Gen 1 hub
USB Power Delivery	65 Watt
Panel Type	VA
Aspect Ratio	21:9
Native Resolution	WQHD 3440 x 1440 at 60 Hz
Pixel Pitch	0.23175 mm
Pixel Per Inch	110
Brightness	250 cd/m ²
Contrast Ratio	3500:1 / 50000000:1 (dynamic)
Colour Gamut	85% NTSC
Response Time	5 ms (grey-to-grey with overdrive)
Vertical Refresh Rate	48 - 100 Hz
Horizontal Refresh Rate	30 - 160 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating, Haze 25%
Backlight Technology	LED backlight
Colour Temperature	6500K
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese
Features	Low Blue Light Mode, Flicker Free technology, Mercury free, arsenic free, 3-sided micro-edge, 8-bit Colour Depth, edge-lit LED backlight
Colour	Black
Dimensions (WxDxH)	80.94 cm x 23.49 cm x 51.8 cm - with stand
Weight	10.51 kg
	Audio
Type	Speakers - stereo
Output Power / Channel	3 Watt
	Connectivity

Interfaces	HDMI (HDCP) ¦ DisplayPort 1.2 (HDCP) ¦ Audio line-out ¦ USB-C upstream/DisplayPort Alt Mode with Power Delivery (HDCP / power up to 65W) ¦ 4 x USB 3.2 Gen 1 ¦ USB (Type B) ¦ KVM
	Mechanical
Display Position Adjustments	Height, tilt
Tilt Angle	-5/+21
Height Adjustment	100 mm
VESA Mounting Interface	100 x 100 mm
	Miscellaneous
Features	Security lock slot (cable lock sold separately), detachable stand, VESA interface support
Cables Included	1 x HDMI cable - 1.8 m ¦ 1 x DisplayPort cable - 1.8 m ¦ 1 x USB-C to USB-C cable - 1.8 m
Mounting Kit	Included
Backlight Life	30,000 hours
Compliant Standards	TUV, VCCI, GS, NOM, WHQL, CB, CCC, FCC, ISO 9241-307, KCC, WEEE, cTUVus, KC, CEL, EPA, EAC, RCM, BIS, low halogen, DisplayPort 1.2, ICE, KES
Localisation	English / Europe
Security Slot Type	Kensington security slot
	Power
Input Voltage	AC 120/230 V (50/60 Hz)
Power Consumption (On mode)	34 W
Power Consumption SDR (On mode)	39 kWh/1000h
Power Consumption (Typical)	48 Watt
Power Consumption Stand by	0.5 Watt
	Software / System Requirements
Included Software	HP Display Center
	Dimensions & Weight
Dimensions & Weight Details	With stand - width: 80.94 cm - depth: 23.49 cm - height: 51.8 cm - weight: 10.51 kg ¦ Without stand - width: 80.94 cm - depth: 11.21 cm - height: 36.69 cm - weight: 7.85 kg
	Dimensions & Weight (Shipping)
Shipping Width	95 cm
Shipping Depth	22.5 cm
Shipping Height	48 cm
Shipping Weight	16.7 kg
	Environmental Standards
TCO Certified	TCO Certified Displays 8, TCO Certified Edge Displays
ENERGY STAR Certified	Yes
	Manufacturer Warranty

Service & Support	Limited warranty - parts and labour - 3 years
-------------------	---

Environmental Parameters

Min Operating Temperature	5 °C
---------------------------	------

Max Operating Temperature	35 °C
---------------------------	-------

Humidity Range Operating	20 - 80% (non-condensing)
--------------------------	---------------------------

Technical data © 1WorldSync. Subject to technical modifications and errors.