

Poly RealPresence Touch - Touchscreen w/ LCD display

multi-touch - wired - Ethernet

Group	PBX Accessories
Manufacturer	Poly
Manufacturer item no.	8200-84190-001
EAN/UPC	0610807857402



Description

Polycom RealPresence Touch is a touch interface for RealPresence Group Series and Polycom's Immersive Telepresence solutions. The simple and intuitive design lets you focus on your conversations instead of the technology. The design is consistent across the Polycom portfolio, whether you're calling from a conference room or using a Polycom desktop, mobile or web client. This makes it easy to use video collaboration from any environment, with an interface that is instantly familiar no matter where you're calling from.

For IT administrators, RealPresence Touch is easy to deploy, with Power over Ethernet for single cable connections. You can also adjust the experience to meet the unique needs of your users. The background image can be customized to match your branding or provide information about the room. Plus the home screen buttons and default screens can be selected by administrators to optimize the experience for their user base, resulting in fewer support calls.

Main features

Product Description	Poly RealPresence Touch - touchscreen - Ethernet
Device Type	Touchscreen
Connectivity Technology	Wired - Ethernet
Display	LCD display - 10.1" - 1280 x 800
Dimensions (WxDxH)	25.2 cm x 17.58 cm x 1.125 cm
Weight	1 kg
Multi-Touch	Yes

Extended details

General	
Device Type	Touchscreen
Width	25.2 cm
Depth	17.58 cm
Height	1.125 cm
Weight	1 kg
Input Device	
Connectivity Technology	Wired
Interface	Ethernet
Multi-Touch	Yes
Display	

Type	LCD display
Diagonal Size	10.1"
Image Aspect Ratio	16:10
Native Resolution	1280 x 800
Horizontal Viewing Angle	178
Expansion / Connectivity	
Interfaces	1 x network / power - RJ-45
Additional Ports	1 x USB 2.0 - 5 pin Micro-USB Type B 1 x USB 2.0 - 4 pin USB Type A
Miscellaneous	
Included Accessories	Stand
Manufacturer Warranty	
Service & Support	Limited warranty - parts and labour - 1 year - carry-in
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C

Technical data © 1WorldSync. Subject to technical modifications and errors.