

Dell P3421W - LED monitor - curved

34" - 3440 x 1440 WQHD @ 60 Hz - IPS - 300 cd/m² - 1000:1 - 5 ms
 - HDMI - DisplayPort - USB-C - black - with 3 years Advanced
 Exchange Basic Warranty - for Latitude 54XX - 55XX - 7420; OptiPlex
 30XX; Precision 3650; Vostro 15 7510; XPS 15 9510

Group	Flat Screens
Manufacturer	Dell
Manufacturer item no.	DELL-P3421WM
EAN/UPC	5397184567722



Description

Productivity that pulls you inFocus like never before on this immersive, curved monitor with a WQHD screen, improved cable management and up to 65W of power delivery.

Main features

Product Description	Dell P3421W - LED monitor - curved - 34"
Device Type	LED-backlit LCD monitor - 34"
Energy Class	Class F
Power Consumption (On mode)	31.5 W
Curved Screen	Yes
Features	KVM Switch, USB 3.2 Gen 1 hub, USB PD 65 Watt
Panel Type	IPS
Aspect Ratio	21:9
Native Resolution	WQHD 3440 x 1440 at 60 Hz
Pixel Pitch	0.2325 mm
Brightness	300 cd/m²
Contrast Ratio	1000:1
Response Time	5 ms (grey-to-grey fast), 8 ms (grey-to-grey normal)
Colour Support	1.07 billion colours
Colour Gamut	99% sRGB
Input Connectors	HDMI, DisplayPort, USB-C
Display Position Adjustments	Height, swivel, tilt
Screen Coating	Anti-glare, 3H Hard Coating
Voltage	AC 100-240 V (50/60 Hz)
Colour	Black

Dimensions (WxDxH) - with stand (lowest position)	81.57 cm x 23.74 cm x 39.11 cm
Weight	10.8 kg
Environmental Standards	TCO Certified Displays 8, ENERGY STAR Qualified EPEAT Gold
Compliant Standards	DisplayPort 1.2, HDCP 2.3
Bundled Services	3 years Advanced Exchange Basic Warranty
Designed For	Latitude 3320, 3420, 3520, 5320, 5320 2-in-1, 5420, 5421, 5520, 5521, 7320, 7420, 7520, 9420, 9520, 9520 2-in-1; OptiPlex 3080, 3090, 5090, 7090; Precision 3240, 3450, 3650; Vostro 13 5310, 14 5410, 15 5510, 15 7510, 5415, 5515, 7500; XPS 13 9310, 15 9510

Extended details	
	General
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class F
Diagonal Size	34"
Curved Screen	Yes (3800R)
Built-in Devices	KVM Switch, USB 3.2 Gen 1 hub
USB Power Delivery	65 Watt
Panel Type	IPS
Aspect Ratio	21:9
Native Resolution	WQHD 3440 x 1440 at 60 Hz
Pixel Pitch	0.2325 mm
Pixel Per Inch	109
Brightness	300 cd/m ²
Contrast Ratio	1000:1
Colour Support	1.07 billion colours
Colour Gamut	99% sRGB
Response Time	5 ms (grey-to-grey fast), 8 ms (grey-to-grey normal)
Vertical Refresh Rate	48 - 85 Hz
Horizontal Refresh Rate	30 - 85 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	WLED

Features	Picture by picture, Flicker Free technology, Dell Easy Arrange, Dell ComfortView, Picture-in-Picture, narrow-bezel design, 8-bit + A-FRC Colour Depth, 3-sided bezeless
Colour	Black
Dimensions (WxDxH)	81.57 cm x 23.74 cm x 39.11 cm - with stand (lowest position)
Weight	10.8 kg
	Connectivity
Interfaces	HDMI DisplayPort 1.2 USB-C upstream/DisplayPort Alt Mode with Power Delivery (power up to 65W) USB 3.2 Gen 1 upstream 2 x USB 3.2 Gen 1 downstream 2 x USB 2.0 downstream
	Mechanical
Display Position Adjustments	Height, swivel, tilt
Tilt Angle	-5/+21
Swivel Angle	60
Height Adjustment	150 mm
	Miscellaneous
Features	VESA interface support, security lock
Cables Included	1 x DisplayPort cable - DisplayPort to DisplayPort 1 x HDMI cable 1 x USB-C 3.2 Gen 1 cable 1 x USB 3.2 Gen 1 upstream cable
Compliant Standards	DisplayPort 1.2, HDCP 2.3
	Power
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption (On mode)	31.5 W
Power Consumption SDR (On mode)	31.5 kWh/1000h
Power Consumption (Typical)	31.5 Watt
Power Consumption (Max)	126 Watt
Power Consumption Stand by	0.3 Watt
Power Consumption (Off Mode)	0.2 Watt
	Software / System Requirements
Included Software	Dell Display Manager
	Dimensions & Weight
Dimensions & Weight Details	With stand (lowest position) - width: 81.57 cm - depth: 23.74 cm - height: 39.11 cm - weight: 10.8 kg Without stand - width: 81.57 cm - depth: 5.81 cm - height: 36.54 cm - weight: 6.7 kg
	Dimensions & Weight (Shipping)

Shipping Weight	14.9 kg
Environmental Standards	
TCO Certified	TCO Certified Displays 8
EPEAT Compliant	EPEAT Gold
ENERGY STAR Certified	Yes
ENERGY STAR Version	8.0
Manufacturer Warranty	
Bundled Services	3 years Advanced Exchange Basic Warranty
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)
Compatibility Information	
Designed For	Dell Latitude 3320, 3420, 3520, 5320, 5320 2-in-1, 5420, 5421, 5520, 5521, 7320, 7320 Detachable, 7420, 7520, 9420, 9520, 9520 2-in-1 Dell OptiPlex 3080, 3090, 5090, 7090 Dell Precision 3240 Compact, 3450 Small Form Factor, 3650 Tower Dell Vostro 13 5310, 14 5410, 15 5510, 15 7510, 5415, 5515, 7500 Dell XPS 13 9310, 13 9310 2-in-1, 15 9510

Technical data © 1WorldSync. Subject to technical modifications and errors.