

HP E34m G4 Conferencing Monitor

E-Series - LED monitor - curved - 34" - 3440 x 1440 WQHD @ 75 Hz
 - VA - 400 cd/m² - 3000:1 - 5 ms - HDMI - DisplayPort - USB-C - speakers

Group	Flat Screens
Manufacturer	HP
Manufacturer item no.	40Z26E9#ABB
EAN/UPC	0196068668518



Description

Conference and connect with ease with the Zoom Certified HP E34m G4 USB-C conferencing monitor that has an integrated 5MP, tiltadjustable webcam, front-firing speakers, and dual mics. Work effortlessly and simplify your set up with one USB-C cable that delivers data, video, and up to 65W of laptop charging.

Main features

Product Description	HP E34m G4 Conferencing Monitor - E-Series - LED monitor - curved - 34"
Device Type	LED-backlit LCD monitor - 34"
Curved Screen	Yes
Features	USB 3.2 Gen 1 hub, 5.0 megapixel IR camera, USB PD 65 Watt
Panel Type	VA
Aspect Ratio	21:9
Native Resolution	WQHD 3440 x 1440 (DisplayPort: 75 Hz, HDMI: 75 Hz, USB-C: 75 Hz)
Brightness	400 cd/m ²
Contrast Ratio	3000:1 / 10000000:1 (dynamic)
Response Time	5 ms (grey-to-grey with overdrive)
Colour Support	16.7 million colours
Colour Gamut	99% sRGB
Input Connectors	HDMI, DisplayPort, USB-C
Built-in Ethernet	Yes
Audio Input	Microphone
Display Position Adjustments	Height, swivel, tilt
Screen Coating	Anti-glare, 3H Hard Coating
Voltage	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH) - with stand	80.83 cm x 23.3 cm x 54.32 cm

Weight	11.98 kg
Localisation	English / Europe
Environmental Standards	ENERGY STAR Qualified
Compliant Standards	TUV GS, VCCI, BSMI, NOM, TUV S, CB, CCC, PSB, FCC, ISO 9241-307, KCC, WEEE, cTUVus, E-Standby, KC, CECP, EAC, CEL Grade 1, ISC, RCM, SEPA, BIS, low halogen, DisplayPort 1.2, Energy-using Products (EuP) Lot 5, ICE, SmartWay, NRCS, Mexico Energy label, Ukraine, UAE, TGM, Belarus Energy

Extended details

	General
Display Type	LED-backlit LCD monitor / TFT active matrix
Diagonal Size	34"
Curved Screen	Yes (1500R)
Built-in Devices	USB 3.2 Gen 1 hub, 5.0 megapixel IR camera
USB Power Delivery	65 Watt
Panel Type	VA
Aspect Ratio	21:9
Native Resolution	WQHD 3440 x 1440 (DisplayPort: 75 Hz, HDMI: 75 Hz, USB-C: 75 Hz)
Brightness	400 cd/m ²
Contrast Ratio	3000:1 / 10000000:1 (dynamic)
Colour Support	16.7 million colours
Colour Gamut	99% sRGB
Response Time	5 ms (grey-to-grey with overdrive)
Vertical Refresh Rate	48 - 75 Hz
Horizontal Refresh Rate	30 - 150 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare, 3H Hard Coating
Backlight Technology	LED backlight
OSD Languages	Chinese (traditional), Chinese (simplified), English, German, French, Italian, Portuguese, Spanish, Dutch, Japanese
Features	HDCP, Flicker Free technology, 3-sided micro-edge, Low Blue Light technology, 8-bit Colour Depth, edge-lit LED backlight, HP Eye Ease, pop-up webcam, Zoom Certified
Dimensions (WxDxH)	80.83 cm x 23.3 cm x 54.32 cm - with stand
Weight	11.98 kg

	Audio Input
Type	Microphone
Microphone Features	Echo cancellation
	Audio
Type	Speakers - stereo
Output Power / Channel	5 Watt
	Connectivity
Interfaces	DisplayPort 1.2 (HDCP) HDMI (HDCP) USB-C 3.2 Gen 1 (power up to 65W) 4 x USB 3.2 Gen 1 LAN Audio line-in/out (mini-jack)
	Mechanical
Display Position Adjustments	Height, swivel, tilt
Tilt Angle	-5/+20
Swivel Angle	60
Height Adjustment	150 mm
VESA Mounting Interface	100 x 100 mm
	Miscellaneous
Features	Security lock slot (cable lock sold separately), detachable stand, VESA interface support
Included Accessories	Mount adapter
Cables Included	1 x USB-C cable
Compliant Standards	TUV GS, VCCI, BSMI, NOM, TUV S, CB, CCC, PSB, FCC, ISO 9241-307, KCC, WEEE, cTUVus, E-Standby, KC, CECP, EAC, CEL Grade 1, ISC, RCM, SEPA, BIS, low halogen, DisplayPort 1.2, Energy-using Products (EuP) Lot 5, ICE, SmartWay, NRCS, Mexico Energy label, Ukraine, UAE, TGM, Belarus Energy
Localisation	English / Europe
Security Slot Type	Kensington security slot
	Power
Input Voltage	AC 120/230 V (50/60 Hz)
Power Consumption (Typical)	65 Watt
Power Consumption (Max)	185 Watt
Power Consumption Stand by	0.5 Watt
	Software / System Requirements
Included Software	HP Display Assistant

Dimensions & Weight	
Dimensions & Weight Details	Without stand - width: 80.83 cm - depth: 10.91 cm - height: 38.81 cm With stand - width: 80.83 cm - depth: 23.3 cm - height: 54.32 cm - weight: 11.98 kg
Dimensions & Weight (Shipping)	
Shipping Width	90.5 cm
Shipping Depth	28.1 cm
Shipping Height	48.1 cm
Shipping Weight	17.69 kg
Environmental Standards	
ENERGY STAR Certified	Yes
Environmental Parameters	
Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	20 - 80% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.