

# Dell S2723HC - LED monitor - 27"

1920 x 1080 Full HD (1080p) @ 75 Hz - IPS - 300 cd/m² - 1000:1 - 4 ms - HDMI - USB-C - speakers - with 3 years Advanced Exchange Basic Warranty

Group	Flat Screens
Manufacturer	Dell
Manufacturer item no.	DELL-S2723HC
EAN/UPC	5397184656884



## Description

27" monitor with the USB-C single-cable solution designed to keep your desktop clutter-free. Featuring built-in speakers and In-Plane Switching (IPS) technology.

## Main features

Product Description	Dell S2723HC - LED monitor - Full HD (1080p) - 27" - with 3-year Basic Advanced Exchange
Device Type	LED-backlit LCD monitor - 27"
Energy Class	Class E
Adaptive-Sync Technology	AMD FreeSync
Features	USB 3.2 Gen 1/USB-C hub, USB PD 65 Watt
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 75 Hz
Pixel Pitch	0.3114 mm
Brightness	300 cd/m²
Contrast Ratio	1000:1
Response Time	4 ms (grey-to-grey extreme), 5 ms (grey-to-grey fast), 8 ms (grey-to-grey normal)
Colour Support	16.7 million colours
Colour Gamut	99% sRGB
Input Connectors	HDMI, USB-C
Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Screen Coating	Anti-glare 3H hardness
Voltage	AC 100-240 V (50/60 Hz)
Dimensions (WxDxH) - with stand (lowest position)	60.99 cm x 17.47 cm x 39.895 cm
Weight	6.15 kg
Compliant Standards	Plug and Play, TUV Rheinland

Bundled Services	3 years Advanced Exchange Basic Warranty
------------------	--

## Extended details

General	
Display Type	LED-backlit LCD monitor / TFT active matrix
Energy Class	Class E
Diagonal Size	27"
Adaptive-Sync Technology	AMD FreeSync
Built-in Devices	USB 3.2 Gen 1/USB-C hub
USB Power Delivery	65 Watt
Panel Type	IPS
Aspect Ratio	16:9
Native Resolution	Full HD (1080p) 1920 x 1080 at 75 Hz
Pixel Pitch	0.3114 mm
Pixel Per Inch	81.57
Brightness	300 cd/m <sup>2</sup>
Contrast Ratio	1000:1
Colour Support	16.7 million colours
Colour Gamut	99% sRGB
Response Time	4 ms (grey-to-grey extreme), 5 ms (grey-to-grey fast), 8 ms (grey-to-grey normal)
Vertical Refresh Rate	48 - 75 Hz
Horizontal Refresh Rate	30 - 90 kHz
Horizontal Viewing Angle	178
Vertical Viewing Angle	178
Screen Coating	Anti-glare 3H hardness
Backlight Technology	LED backlight
Features	LED edgelight system, Flicker Free technology, Premium Panel Guarantee, Dell Easy Arrange, Eye comfort mode, Low Blue Light technology, 3-sided bezelless, 6-bit + Hi-FRC Color Depth
Dimensions (WxDxH)	60.99 cm x 17.47 cm x 39.895 cm - with stand (lowest position)
Weight	6.15 kg
Audio	
Type	Speakers - stereo
Output Power / Channel	3 Watt
Connectivity	
Interfaces	HDMI (HDCP 1.4)   USB-C upstream/DisplayPort 1.2 Alt Mode with Power Delivery (power up to 65W)   USB 3.2 Gen 1 downstream (power up to 10W)   USB 3.2 Gen 1 downstream   Audio line-out
Mechanical	

Display Position Adjustments	Height, pivot (rotation), swivel, tilt
Tilt Angle	-5/+21
Swivel Angle	60
Rotation Angle	180
Height Adjustment	110 mm
VESA Mounting Interface	100 x 100 mm
	<b>Miscellaneous</b>
Features	Security lock slot (cable lock sold separately), VESA interface support
Cables Included	1 x USB-C 3.2 Gen 1 cable - 1.8 m
Compliant Standards	Plug and Play, TUV Rheinland
Security Slot Type	Kensington security slot
	<b>Power</b>
Input Voltage	AC 100-240 V (50/60 Hz)
Power Consumption SDR (On mode)	17.3 kWh/1000h
Power Consumption (Max)	135 Watt
Power Consumption Stand by	0.3 Watt
Power Consumption (Off Mode)	0.3 Watt
On / Off Switch	Yes
	<b>Software / System Requirements</b>
Included Software	Dell Display Manager
	<b>Dimensions &amp; Weight</b>
Dimensions & Weight Details	With stand (lowest position) - width: 60.99 cm - depth: 17.47 cm - height: 39.895 cm - weight: 6.15 kg   With stand (highest position) - width: 60.99 cm - depth: 17.47 cm - height: 50.895 cm - weight: 6.15 kg   Without stand - width: 60.99 cm - depth: 5.403 cm - height: 36.364 cm - weight: 4.65 kg
	<b>Dimensions &amp; Weight (Shipping)</b>
Shipping Weight	8.99 kg
	<b>Manufacturer Warranty</b>
Bundled Services	3 years Advanced Exchange Basic Warranty
	<b>Environmental Parameters</b>
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 80% (non-condensing)

Technical data © 1WorldSync. Subject to technical modifications and errors.

