

Zebra XSLATE L10 - Rugged - tablet

Intel Core i5 8250U / 1.6 GHz - Win 10 Pro 64-bit - UHD Graphics 620
 - 8 GB RAM - 128 GB SSD - 10.1" touchscreen 1920 x 1200 - Wi-Fi 5 - 4G LTE

Group	Tablets
Manufacturer	Zebra
Manufacturer item no.	RSL10-LSV5W4W4S0P0X0



Description

It is more important than ever to give workers the right mobility tools. They need a reliable way to capture, extract, and analyze data about your customers, assets, and revenue-generating opportunities, especially when they are away from their desks. Whether your business is public safety, utilities, or manufacturing, the XSLATE L10 rugged tablet computer will enable you to drive greater business efficiency among your mobile workforce, for a much longer period of time.

Main features

Product Description	Zebra XSLATE L10 - 10.1" - Core i5 8250U - 8 GB RAM - 128 GB SSD - 4G LTE
Product Type	Tablet - no keyboard - rugged
Operating System	Win 10 Pro 64-bit
Processor	Intel Core i5 (8th Gen) 8250U / 1.6 GHz (3.4 GHz) / 6 MB Cache
Memory	8 GB LPDDR3
Storage	128 GB SSD
Display	10.1" touchscreen 1920 x 1200 / WUXGA
Graphics	Intel UHD Graphics 620
Integrated Webcam	Yes
Networking	802.11a/b/g/n/ac, Bluetooth 4.2
Wireless Broadband (WWAN)	4G LTE
Battery	Up to 10 hours
Features	GNSS receiver
Dockable	Yes
Security	Trusted Platform Module (TPM 2.0) Security Chip, fingerprint reader
Dimensions (WxDxH)	28.08 cm x 19.52 cm x 2.2 cm
Weight	1.3 kg
Localisation	Region: Europe
Environmental Standards	ENERGY STAR Qualified EPEAT Silver

Extended details

General	
Product Type	Tablet - no keyboard - rugged

Operating System	Windows 10 Pro 64-bit Edition
Processor / Chipset	
CPU	Intel Core i5 (8th Gen) 8250U / 1.6 GHz
Max Turbo Speed	3.4 GHz
Cache	6 MB
Features	Intel Turbo Boost Technology
Memory	
RAM	8 GB
Technology	LPDDR3 SDRAM
Storage	
Main Storage	128 GB SSD PCIe
Display	
Type	10.1"
Touchscreen	Yes (10-point multi-touch)
Resolution	1920 x 1200 (WUXGA)
Widescreen	Yes
Image Aspect Ratio	16:10
Image Brightness	1000 cd/m ²
Features	View Anywhere, anti-glare, Corning Gorilla glass 3, Hard Coating (3H), glove touch mode, wet touch mode, Wide Viewing Angle, night vision mode, capacitive touch screen
Audio & Video	
Graphics Processor	Intel UHD Graphics 620
Camera	Yes
Resolution	13 Megapixel (rear), 2 Megapixel (front)
Sound	Speaker, array microphone
Compliant Standards	High Definition Audio
Communications	
Wireless	802.11a/b/g/n/ac, Bluetooth 4.2
Wireless Controller	Intel Dual Band Wireless-AC 8265
Wireless Broadband (WWAN)	
Generation	4G
Technology	LTE
Controller	Sierra Wireless EM7565
Navigation	
Receiver	GPS/GLONASS/Galileo/BeiDou
Battery	
Run Time	Up to 10 hours
AC Adapter	
Output	19 V

	Connections & Expansion
Slots	2 x Nano-SIM card (2 free)
Interfaces	2 x USB 3.0 USB-C 3.0 (supports DisplayPort Alt Mode) LAN Audio line-in/out Dock RF pass-through
Memory Card Reader	Yes (microSD, microSDXC)
	Software
Software Included	Pen and Touch Enabled BIOS Setup, Know Your Tablet
	Miscellaneous
Case Material	Magnesium alloy
Integrated Options	GNSS receiver
Dockable	Yes
Security	Trusted Platform Module (TPM 2.0) Security Chip, fingerprint reader
Features	Water-resistant, dust-resistant, shock-resistant, drop-resistant, UEFI BIOS, vibration
Theft/Intrusion Protection	Security lock slot (cable lock sold separately)
Security Slot Type	Kensington security slot
Included Accessories	Power adapter
Compliant Standards	EN 61000-3-2, EN 61000-3-3, EN55024, FCC Part 15 B, MIL-STD 810G, IP65, EN 62311, AS/NZS 60950-1 Second Edition, EN 301 489, EN 62209-2, EN 62209-2:2010, NOM-019, RoHS 2 (2011/65/EU), EN 55032 Class B, WEEE 2012/19/EC, ANSI/ISA 12.12.01-2013, Directive 2013/56/EU, IEC/EN 60950-1, UL/CSA60950-1 (2nd Edition), EN 303 413
Localization	Region: Europe
	Dimensions & Weight
Dimensions (WxDxH)	28.08 cm x 19.52 cm x 2.2 cm
Weight	1.3 kg
	Environmental Standards
EPEAT Compliant	EPEAT Silver
ENERGY STAR Certified	Yes
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years
	Environmental Parameters
Min Operating Temperature	-20 °C
Max Operating Temperature	60 °C
Humidity Range Operating	3 - 95% (non-condensing)
Shock Tolerance (operating)	40 g

Technical data © 1WorldSync. Subject to technical modifications and errors.