

APC Smart-UPS 750 LCD - UPS - AC 230 V

500 Watt - 750 VA - RS-232 - USB - output connectors: 6 - black - for
P/N: AR4018SPX431 - AR4018SPX432 - AR4024SP - AR4024SPX429
- AR4024SPX431 - AR4024SPX432

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMT750I
EAN/UPC	0731304269069



Description

APC Smart-UPS protects your data by supplying reliable, network-grade power in either traditional Tower or Rack-optimized form factors for space constrained business critical applications. Award winning APC Smart-UPS is the perfect UPS for protecting business critical fileservers (Intel or UNIX based), minicomputers, network switches and hubs, Point of Sale, retail/bank back office and ATMs. Rack Mount versions are the choice for rack optimized servers, server appliances, blade servers, other blade devices and rack-mounted network switches and hubs.

Main features

Product Description	APC Smart-UPS 750 LCD - UPS - 500 Watt - 750 VA
Device Type	UPS - external
Weight	13.18 kg
Input Voltage	AC 230 V
Output Voltage	AC 230 V
Power Capacity	500 Watt / 750 VA
Input Connectors	Power IEC 60320 C14
Output connectors	6 x power IEC 60320 C13
Battery	Lead Acid
Run Time (Up To)	5 min at full load
Networking	RS-232, USB
Colour	Black
Dimensions (WxDxH)	13.8 cm x 36.3 cm x 16.1 cm
Designed For	P/N: AR4000MVX429, AR4000MVX432, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429

Extended details

General	
Device Type	UPS - external
Colour	Black

	Power Device
UPS Technology	Line interactive
Input Voltage	AC 230 V
Input Voltage Range	AC 160 - 280 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Provided	47 - 53 / 57 - 63 Hz
Frequency Required	50/60 Hz
Input Connectors	Power IEC 60320 C14
Power Output Connectors Details	6 x power IEC 60320 C13
Output Voltage	AC 230 V 47 - 53 / 57 - 63 Hz
Power Capacity	500 Watt / 750 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	540 Joules
	Battery
Technology	Lead Acid
Run Time (Up To)	5 min at full load
	Networking
Remote Management Interface	RS-232, USB
	Expansion / Connectivity
Interfaces	1 x management (RS-232) - 9 pin D-Sub (DB-9) 1 x USB
Expansion Slots	1 SmartSlot
	Miscellaneous
Features	Audible alarm, LCD display
Compliant Standards	C-Tick, UL 1449, VDE, EN 50091-2, RoHS, EN 50091-1, REACH
	Manufacturer Warranty
Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	40 dBA
	Dimensions & Weight
Width	13.8 cm
Depth	36.3 cm
Height	16.1 cm
Weight	13.18 kg
	Compatibility Information

Designed For

P/N: AR4000MV, AR4000MVX429, AR4000MVX432, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X431, AR4038X432

Technical data © 1WorldSync. Subject to technical modifications and errors.