

APC Smart-UPS SMT750IC - UPS - AC 220/230/240 V

500 Watt - 750 VA - RS-232 - USB - output connectors: 6 - black - with APC SmartConnect - for P/N: AR4018SPX431 - AR4018SPX432 - AR4024SP - AR4024SPX429 - AR4024SPX431 - AR4024SPX432

Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMT750IC
EAN/UPC	0731304340317



Description

APC Smart-UPS protects your data by supplying reliable, network-grade power for space constrained business critical applications. Award winning APC Smart-UPS is the perfect UPS for protecting business critical file servers, minicomputers, network switches and hubs, Point of Sale, retail/bank back office and ATMs.

Main features

Product Description	APC Smart-UPS SMT750IC - UPS - 500 Watt - 750 VA - with APC SmartConnect
Device Type	UPS - external
Weight	13.18 kg
Input Voltage	AC 220/230/240 V
Output Voltage	AC 230 V $\pm$ 5%
Power Capacity	500 Watt / 750 VA
Input Connectors	1 x power IEC 60320 C14
Output connectors	6 x power IEC 60320 C13 2 x IEC jumper
Battery	Lead Acid
Batteries Qty	1
Run Time (Up To)	4.6 min at full load
Networking	RS-232, USB
Colour	Black
Dimensions (WxDxH)	13.8 cm x 35.81 cm x 15.75 cm
Bundled with	APC SmartConnect

Designed For

P/N: AR4000MVX429, AR4000MVX432, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X432, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4038IX429, AR4038IX431, AR4038IX432

Extended details

	General
Device Type	UPS - external
Colour	Black
Bundled with	APC SmartConnect
	Power Device
UPS Technology	Line interactive
Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 160 - 286 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Provided	50/60 Hz ± 3Hz
Frequency Required	50/60 Hz ± 3Hz
Input Connectors	1 x power IEC 60320 C14
Power Output Connectors Details	6 x power IEC 60320 C13 2 x IEC jumper
Output Voltage	AC 230 V ± 5% - 50/60 Hz
Power Capacity	500 Watt / 750 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	540 Joules
Circuit Protection	Circuit breaker
	Battery
Quantity	1
Technology	Lead Acid

Run Time (Up To)	4.6 min at full load 15.9 min at half load 103 min at 50 Watts 50.5 min at 100 Watts 21.7 min at 200 Watts 12 min at 300 Watts 7.3 min at 400 Watts
Recharge Time	3 hours
Transfer Time	6 ms
Features	Maintenance free, sealed, leak-proof
	Networking
Remote Management Interface	RS-232, USB
	Expansion / Connectivity
Interfaces	1 x management (RS-232) - RJ-45 1 x management (USB)
Expansion Slots	1 (total) / 1 (free) x SmartSlot
	Miscellaneous
Cables Included	Serial cable - external USB cable - external Power cable 1.83 m
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), cold-start function, automatic self-test, predictive failure notification, hot-swappable batteries, energy metre
Compliant Standards	CSA, UL 1778, VDE, IEC 62040-2, RoHS, REACH, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1
	Software / System Requirements
Software Included	APC PowerChute Business Edition
	Manufacturer Warranty
Service & Support	Limited warranty - replace or repair - 3 years Limited warranty - batteries - 2 years
	Environmental Parameters
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	40 dBA
	Dimensions & Weight
Width	13.8 cm
Depth	35.81 cm
Height	15.75 cm
Weight	13.18 kg
	Dimensions & Weight (Shipping)

Shipping Width	27.8 cm
Shipping Depth	39.9 cm
Shipping Height	30.1 cm
Shipping Weight	14.23 kg
Compatibility Information	
Designed For	P/N: AR4000MV, AR4000MVX429, AR4000MVX432, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X432

Technical data © 1WorldSync. Subject to technical modifications and errors.