

HPE ProLiant DL160 Gen10 - Server

rack-mountable - 1U - 2-way - 1 x Xeon Bronze 3204 / 1.9 GHz - RAM 16 GB - SATA - hot-swap 3.5" bay(s) - no HDD - GigE - monitor: none

Group	Servers
Manufacturer	HPE
Manufacturer item no.	P19559-B21
EAN/UPC	0190017381831



Description

HPE ProLiant DL160 Gen10 - Server - rack-mountable - 1U - 2-way - 1 x Xeon Bronze 3204 / 1.9 GHz - RAM 16 GB - SATA - hot-swap 3.5" bay(s) - no HDD - GigE - monitor: none

Main features

Product Description	HPE ProLiant DL160 Gen10 - rack-mountable - Xeon Bronze 3204 1.9 GHz - 16 GB - no HDD
Type	Server - rack-mountable
Height (Rack Units)	1U
Server Scalability	2-way
Processor	1 x Intel Xeon Bronze 3204 / 1.9 GHz (6-core)
Cache Memory	8.25 MB
Cache Per Processor	8.25 MB
RAM	16 GB (installed) / 256 GB (max) - DDR4 SDRAM
Storage Controller	SATA (SATA 6Gb/s) - PCIe 3.0 x4 (HPE Smart Array S100i)
Server Storage Bays	Hot-swap 3.5"
Hard Drive	No HDD
Optical Storage	No optical drive
Video Memory	16 MB
Networking	GigE
Power	AC 120/230 V (50/60 Hz)
Power Redundancy	Optional
Dimensions (WxDxH)	43.46 cm x 61.49 cm x 4.29 cm
Weight	13.92 kg

Extended details

	General
Type	Server
Product Form Factor	Rack-mountable - 1U

Server Scalability	2-way
Hot-Swap Bays Qty	4
Processor / Chipset	
CPU	Intel Xeon Bronze 3204
Clock Speed	1.9 GHz
Number of Cores	6-core
CPU Qty	1
Max CPU Qty	2
CPU Upgradability	Upgradable
Chipset Type	Intel C622
Cache Memory	
Installed Size	8.25 MB
Cache Per Processor	8.25 MB
RAM	
Installed Size	16 GB / 256 GB (max)
Technology	DDR4 SDRAM
Effective Memory Speed	2133 MHz
Rated Memory Speed	2666 MHz
Form Factor	DIMM 288-pin
Slots	8 (Total) / 7 (empty)
Features	Registered
Configuration Features	1 x 16 GB
Hard Drive	
Type	No HDD
Storage Controller	
Type	1 x SATA - PCIe 3.0 x4
Controller Interface Type	SATA 6Gb/s
Storage Controller Name	HPE Smart Array S100i
Channel Qty	14
RAID Level	RAID 0, RAID 1, RAID 5, RAID 10
Optical Storage	
Type	No optical drive
Monitor	
Monitor Type	None.
Graphics Controller	
Video Memory	16 MB
Video Interfaces	VGA
Networking	
Ethernet Ports	2 x Gigabit Ethernet

Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Protocol	SNMP 3, IPMI 2.0
Features	Wake on LAN (WoL), PXE support
Expansion / Connectivity	
Bays	4 (total) / 4 (free) x hot-swap 3.5" LFF
Slots	1 (total) / 1 (free) x microSD Card (internal) 1 (total) / 1 (free) x FlexibleLOM (x8 mode) 1 (total) / 1 (free) x PCIe 3.0 x8 - half-length, half-height
Interfaces	1 x VGA 2 x LAN (Gigabit Ethernet) 1 x HPE iLO 1 x management 4 x USB 3.0 (1 front, 2 rear, 1 internal)
Miscellaneous	
Compliant Standards	WEEE, ASHRAE Class A4, ASHRAE Class A3, ACPI 6.1
Power	
Device Type	Power supply - hot-plug
Power Redundancy	Optional
Power Redundancy Scheme	1+1 (with optional power supply)
Installed Qty	1
Max Supported Qty	2
Voltage Required	AC 120/230 V (50/60 Hz)
Power Provided	500 Watt
80 PLUS Certification	80 PLUS Platinum
Manufacturer Warranty	
Service & Support	Limited warranty - parts and labour - 3 years - on-site
Dimensions & Weight	
Width	43.46 cm
Depth	61.49 cm
Height	4.29 cm
Weight	13.92 kg
Environmental Parameters	
Min Operating Temperature	10 °C
Max Operating Temperature	35 °C
Humidity Range Operating	8 - 90% (non-condensing)
Sound Emission	28.1 dBA

Technical data © 1WorldSync. Subject to technical modifications and errors.