

Lexmark MX321adn - Multifunction printer

B/W - laser - 215.9 x 355.6 mm (original) - A4/Legal (media) - up to 36 ppm (copying) - up to 36 ppm (printing) - 350 sheets - 33.6 Kbps - USB 2.0 - LAN

Group	Multifunction Printers
Manufacturer	Lexmark
Manufacturer item no.	36S0630
EAN/UPC	0734646639149



Description

The Lexmark MX321adn offers fax, automatic document feeder, and copy functions, all powered by a standard multi-core processor.

Main features

Product Description	Lexmark MX321adn - multifunction printer - B/W
Device Type	Multifunction printer
Fax Type	Super G3 - plain paper
Printing Technology	Laser (monochrome)
Monthly Duty Cycle (max)	50000 pages
Recommended Monthly Volume	500 - 6000 pages
Max Copying Speed	Up to 36 ppm
Max Printing Speed	Up to 36 ppm
Max Printing Resolution	Up to 1200 x 1200 dpi
Max Printing Resolution Class	Up to 1200 x 1200 dpi
Max Fax Transmission Speed	33.6 Kbps
Scanning	600 x 600 dpi
Original Size	215.9 x 355.6 mm (max)
Original Type	Sheets

Document Feeder Capacity	50 sheets
Media Size	Legal (216 x 356 mm), A4 (210 x 297 mm) (max)
Media Type	Transparencies, envelopes, plain paper, labels, card stock
Standard Media Capacity	350 sheets
Max Media Capacity	900 sheets
Bypass Feeder Capacity	100 sheets
Output Trays Capacity	150 sheets
Automatic Duplexing	Yes (copying) Yes (printing) Yes (scanning)
Connection Availability	Yes
Interface	USB 2.0, LAN
AirPrint Enabled	Yes
Office Machine Features	Scan to e-mail, scan to network, scan to FTP
Dimensions (WxDxH)	39.9 cm x 42.95 cm x 46.7 cm
Weight	19.4 kg
Environmental Standards	ENERGY STAR Qualified, Blue Angel

Extended details	
	General
Printer Fonts	Scalable PPDS x 39 Bitmapped PPDS x 5 Scalable PCL x 84 Scalable PostScript x 91 Bitmapped PCL x 2
Device Type	Multifunction printer
Fax Type	Plain paper
Printing Technology	Laser - monochrome
Monthly Duty Cycle (max)	50000 pages
Recommended Monthly Volume	500 - 6000 pages
Display Colour Support	Colour

Connection Availability	Yes
Interface	USB 2.0, LAN
AirPrint Enabled	Yes
Office Machine Features	Scan to e-mail, scan to network, scan to FTP
	Memory
Standard Memory	1 GB
Max Supported Memory	1 GB
	Copying
Max Copying Speed	Up to 36 ppm
Max Document Enlargement	400%
Max Document Reduction	25%
Automatic Duplexing	Yes
	Printing
Max Printing Resolution	Up to 1200 x 1200 dpi
Max Printing Resolution Class	Up to 1200 x 1200 dpi
Max Printing Speed	Up to 36 ppm
Image Enhancement Technology	1200 IQ, 2400 IQ
Automatic Duplexing	Yes
First Print Out Time B/W	6.5 sec
	Scanning
Scan Element	CIS
Automatic Duplexing	Yes
Optical Resolution	600 x 600 dpi
	Fax Machine

Compatibility	Super G3
Max Transmission Speed	33.6 Kbps
	Document & Media Handling
Max Original Size	215.9 x 355.6 mm
Original Type	Sheets
Document Feeder Capacity	50 sheets
Max Media Size	A4/Legal
Supported Media Type	Transparencies, envelopes, plain paper, labels, card stock
Supported Media Sizes	ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), A6 (105 x 148 mm), Folio (216 x 330 mm), JIS B5 (182 x 257 mm), Statement (139.7 x 215.9 mm), Oficio (216 x 343 mm)
Supported Envelope Sizes	US No 10 (104.7 x 241.3 mm), International DL (110 x 220 mm), Monarch (98.4 x 190.5 mm), US No 9 (98.6 x 225.6 mm)
Standard Media Capacity	350 sheets
Max Media Capacity	900 sheets
Bypass Feeder Capacity	100 sheets
Output Trays Capacity	150 sheets
Document & Media Handling Details	Bypass tray - 100 sheets Input tray - 250 sheets weight: 60 g/m ² - 120 g/m ² ADF - 50 sheets Output tray - 150 sheets
Speed Details	Printing: up to 36 ppm (A4) - B/W Printing: up to 19 spm (A4) - B/W duplex Copying: up to 36 ppm (A4) - B/W Copying: up to 19 spm (A4) - B/W duplex Scanning: up to 42 spm (A4) - B/W Scanning: up to 45 spm (Letter A) - B/W Scanning: up to 20 spm (A4) - colour Scanning: up to 22 spm (Letter A) - colour
	Connections
Interfaces	1 x USB 2.0 - 4 pin USB Type B 1 x LAN - RJ-45
Security Protocols & Features	SSL, LEAP, TLS, IPsec, 802.1x, ARP, TTLS, PEAP, MD5, MS-CHAPv2

Operating System Support	Novell NetWare 6, SuSE Linux Enterprise Server 10, SuSE Linux Enterprise Server 11, Sun Solaris 10, Novell NetWare 5.1, Novell NetWare 6.5, IBM AIX 6.1, Apple Mac OS X 10.6, Apple Mac OS X 10.7, Red Hat Enterprise Linux WS 6.0, IBM AIX 7.1, Apple Mac OS X 10.8, Apple Mac OS X 10.9, MS Windows 7 (32/64 bits), Debian Linux 7.0, Sun Solaris 11, Apple Mac OS X 10.10, Windows 8 (32/64-bits), Windows 8.1 (32/64-bits), Windows 10, Apple Mac OS X 10.11, openSUSE 13.2, Novell Open Enterprise Server 2, Debian Linux 8.0, SuSE Linux Enterprise Server 12, Novell Open Enterprise Server 11, Red Hat Enterprise Linux WS 7.0, macOS 10.12, Ubuntu Linux 16.04, Fedora Linux 23, Fedora Linux 24, openSUSE 42.3
Software Included	Drivers & Utilities
	Power
Power Consumption Operational	520 Watt
Power Consumption Standby	10.5 Watt
Power Consumption Sleep	0.1 Watt
	Miscellaneous
First Copy Out Time B/W	6.5 sec
Consumables Included	1 x Cartridge - up to 2500 pages ISO/IEC 19752 1 x imaging unit - up to 60000 pages at 5% coverage
Compliant Standards	FCC Class B certified, C-Tick, NOM, ICES-003 Class B, CCC, DOC, SII, UL 60950-1, IEC 60950-1, EN 60950-1, BSMI Class B, KCC, IEC 60825-1, FDA, UL-AR, GOST-R, EN 60825-1, KC, CECP, CEL, VCCI Class B, ECMA-370, EFTA, TER, MET, ISO 532B, TED, CAN/CSA-C22.2 No. 60950-1
	Environmental Standards
ENERGY STAR Certified	Yes
Blue Angel Compliant	Yes
	Manufacturer Warranty
Service & Support	Limited warranty - 1 year - on-site - response time: next business day
	Dimensions & Weight
Width	39.9 cm
Depth	42.95 cm
Height	46.7 cm
Weight	19.4 kg
	Dimensions & Weight (Shipping)
Shipping Width	48.4 cm
Shipping Depth	52.4 cm
Shipping Height	56.4 cm

Shipping Weight	22.25 kg
Environmental Parameters	
Sound Emission	14 dBA (idle) / 54 dBA (operating)
Min Operating Temperature	10 °C
Max Operating Temperature	32 °C
Humidity Range Operating	8 - 80%

Technical data © 1WorldSync. Subject to technical modifications and errors.