

HPE StoreOnce 5200 Base System

NAS server - 12 bays - rack-mountable - SAS - RAID 6 - 10 Gigabit Ethernet / Gigabit Ethernet / 8Gb Fibre Channel - iSCSI support - 2U

Group	Software
Manufacturer	HPE
Manufacturer item no.	BB956A
EAN/UPC	0190017208763



Description

HPE StoreOnce protects small, remote offices to enterprise data centers with highly scalable dedicated appliances and agile virtual appliances and with your choice of backup and recovery software to deliver robust, flexible enterprise-wide data protection. StoreOnce can reduce the amount of backup data you need to store.

Main features

Product Description	HPE StoreOnce 5200 Base System - NAS server
Device Type	NAS server
Host Connectivity	10 Gigabit Ethernet / Gigabit Ethernet / 8Gb Fibre Channel
Enclosure Type	Rack-mountable - 2U
Max Supported Capacity	288 TB
Installed Devices / Modules Qty	0 (installed) / 12 (max)
Weight	)
Storage Controller	RAID SAS RAID 6
Networking	GigE, 10 GigE, 8Gb Fibre Channel
Power	AC 120/230 V (50/60 Hz)

Extended details

	General
Device Type	NAS server
Host Connectivity	10 Gigabit Ethernet / Gigabit Ethernet / 8Gb Fibre Channel
Enclosure Type	Rack-mountable - 2U
Total Storage Capacity	0 TB
Max Supported Capacity	288 TB
Installed Devices / Modules Qty	0 (installed) / 12 (max)

Weight	)
Storage Controller	
Type	RAID
Interface Type	SAS
RAID Level	RAID 6
Networking	
Data Link Protocol	GigE, 10 GigE, 8Gb Fibre Channel
Network Services Compatibility	Microsoft CIFS, Network File System (NFS)
Expansion / Connectivity	
Expansion Bays	12 (total) / 12 (free) - 3.5" LFF
Interfaces	4 x Ethernet 1000 8 x 8Gb Fibre Channel / Ethernet 10Gb
Miscellaneous	
Cables Included	2 x network cable - 3 m
Compliant Standards	EAC
Included Accessories	Rack mounting kit
Power	
Power Device	Internal power supply
Voltage Required	AC 120/230 V (50/60 Hz)
Software / System Requirements	
Software Included	Drivers & Utilities
Environmental Parameters	
Min Operating Temperature	10 °C
Max Operating Temperature	35 °C
Humidity Range Operating	8 - 90%
Sound Emission	39 dBA

Technical data © 1WorldSync. Subject to technical modifications and errors.