

HPE Mixed Use - SSD - 960 GB - hot-swap

2.5" SFF - SATA 6Gb/s - with HPE Smart Carrier

Group	HDDs
Manufacturer	HPE
Manufacturer item no.	P07926-B21
EAN/UPC	0190017306629



Description

Do you need more performance from your HPE ProLiant Sever series or HPE Synergy platforms? HPE Solid State Drives (SSDs) deliver exceptional performance and endurance while reducing power consumption for customers with applications requiring high random read and write IOPs performance. Categorized by Read Intensive (RI), Mixed Use (MU), and Write Intensive (WI), you can choose the right SSD that tailors to your workload demands. Also, you can prevent data loss and monitor the SSD life with HPE SmartSSD Wear Gauge compatibility in management tools. Leveraging NAND Flash technology, they support HPE ProLiant servers including Gen9 and server storage platforms. Available as Small Form Factor (SFF) and Large Form Factor (LFF) hot plug devices, non-hot plug SFF devices, and SFF Quick Release devices, you have great flexibility in your installation. These drives deliver higher performance, better latency, and more power-efficient solutions when compared with traditional rotating media.

Main features

Product Description	HPE Mixed Use - SSD - 960 GB - SATA 6Gb/s
Type	Solid state drive - hot-swap
Capacity	960 GB
Form Factor	2.5" SFF
Interface	SATA 6Gb/s
Features	Digitally Signed Firmware
Bundled with	HPE Smart Carrier
Designed For	Nimble Storage dHCI Large Solution with HPE ProLiant DL380 Gen10, Medium Solution with HPE ProLiant DL325 Gen10; ProLiant BL460c Gen10, DL180 Gen10, DL20 Gen10, DL20 Gen9, DL325 Gen10, DL360 Gen9, DL380 Gen10, DL380 Gen9, DL385 Gen10, DL560 Gen10, ML110 Gen10, ML350 Gen10, WS460c Gen9; Synergy 680 Gen9

Extended details

	General
Device Type	Solid state drive - hot-swap
Capacity	960 GB
Form Factor	2.5" SFF
Interface	SATA 6Gb/s
Features	Digitally Signed Firmware
Bundled with	HPE Smart Carrier

Internal Data Rate	600 MBps
Expansion & Connectivity	
Interfaces	1 x SATA 6 Gb/s
Compatible Bay	2.5" SFF
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years
Compatibility Information	
Designed For	HPE Nimble Storage dHCI Large Solution with HPE ProLiant DL380 Gen10 (2.5"), Medium Solution with HPE ProLiant DL325 Gen10 Plus (2.5") ; HPE ProLiant BL460c Gen10 (2.5"), DL180 Gen10 SMB (2.5"), DL20 Gen10 (2.5"), DL20 Gen10 Entry (2.5"), DL20 Gen10 Performance (2.5"), DL20 Gen10 solution (2.5"), DL20 Gen9 Solution (2.5"), DL325 Gen10 (2.5"), DL325 Gen10 Base (2.5"), DL325 Gen10 Entry (2.5"), DL325 Gen10 Performance (2.5"), DL325 Gen10 Plus (2.5"), DL325 Gen10 Plus All-NVMe Flash Node for Qumulo (2.5"), DL325 Gen10 Plus All-NVMe Flash Node for Software Defined Storage (2.5"), DL325 Gen10 Plus for Weka Expansion Tracking (2.5"), DL325 Gen10 SMB Solution (2.5"), DL325 Gen10 Solution (2.5"), DL360 Gen9 High Performance (2.5"), DL380 Gen10 (2.5"), DL380 Gen10 All Flash Server for Datera (2.5"), DL380 Gen10 Base (2.5"), DL380 Gen10 Entry (2.5"), DL380 Gen10 Entry SMB (2.5"), DL380 Gen10 for Cohesity DataPlatform (2.5"), DL380 Gen10 for SAP HANA Compute Block (2.5"), DL380 Gen10 High Performance (2.5"), DL380 Gen10 Hybrid Server for Datera (2.5"), DL380 Gen10 Network Choice (2.5"), DL380 Gen10 Network Choice for CTERA (2.5"), DL380 Gen10 Performance (2.5"), DL380 Gen10 Server for CTERA (2.5"), DL380 Gen10 SMB (2.5"), DL380 Gen10 SMB Networking Choice (2.5"), DL380 Gen10 Solution (2.5"), DL385 Gen10 Plus (2.5"), DL385 Gen10 Plus Entry (2.5"), DL560 Gen10 (2.5"), DL560 Gen10 Base (2.5"), DL560 Gen10 Entry (2.5"), DL560 Gen10 for SAP HANA Compute Block (2.5"), DL560 Gen10 Performance (2.5"), ML110 Gen10 (2.5"), ML110 Gen10 Entry (2.5"), ML110 Gen10 Performance (2.5"), ML110 Gen10 Solution (2.5"), ML350 Gen10 (2.5"), ML350 Gen10 Base (2.5"), ML350 Gen10 Entry (2.5"), ML350 Gen10 High Performance (2.5"), ML350 Gen10 Performance (2.5"), ML350 Gen10 SMB (2.5"), ML350 Gen10 Solution (2.5"), ML350 Gen10 Special Server (2.5"), ML350 Gen10 Sub-Entry (2.5") ; HPE Synergy 680 Gen9 4S-EX Compute Module (2.5")

Technical data © 1WorldSync. Subject to technical modifications and errors.