

APC Smart-UPS 1000VA LCD RM - UPS (rack-mountable)

AC 220/230/240 V - 700 Watt - 1000 VA - Ethernet 10/100 - RS-232 - USB - output connectors: 4 - 2U - black - with APC SmartConnect - for P/N: AR4018SPX432 - AR4024SP - AR4024SPX429 - AR4024SPX431 - AR4024SPX432 - NBWL0356A



Group	Power Supply
Manufacturer	APC
Manufacturer item no.	SMT1000RMI2UC
EAN/UPC	0731304332985

Description

Intuitive LCD interface provides clear information with the ability to configure the UPS locally with easy-to-use navigation keys. Many different programmable settings including switched outlet group control allow for application specific settings, thresholds and notifications.

Main features

Product Description	APC Smart-UPS 1000VA LCD RM - UPS - 700 Watt - 1000 VA - with APC SmartConnect
Device Type	UPS - rack-mountable
Rack Size	2U
Weight	28.18 kg
Input Voltage	AC 220/230/240 V
Output Voltage	AC 220/230/240 V
Power Capacity	700 Watt / 1000 VA
Input Connectors	Power IEC 60320 C14
Output connectors	4 x power IEC 60320 C13
Battery	Lead Acid
Run Time (Up To)	8.5 min at full load
Networking	Ethernet 10/100, RS-232, USB
Remote Management Protocol	SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, SSH, SSH-2
Colour	Black
Dimensions (WxDxH)	47.7 cm x 43.2 cm x 8.6 cm
Environmental Standards	ENERGY STAR
Bundled with	APC SmartConnect
Designed For	P/N: AR2487G, AR3100W, AR3105SP, AR3105W, AR3140G, AR3140W, AR3150W, AR3155SP, AR3155W, AR3300W, AR3305W, AR3340G, AR3355SP, AR3355W, AR4018IX429, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4024IX431, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4038IX432, NBWL0356A

Extended details

General

Device Type	UPS - rack-mountable
Height (Rack Units)	2U
Colour	Black
Bundled with	APC SmartConnect

Power Device

UPS Technology	Line interactive
Input Voltage	AC 220/230/240 V
Input Voltage Range	AC 160 - 280 V
Input Voltage Range (Adjustable)	AC 151 - 302 V
Frequency Provided	57 - 63 Hz
Frequency Required	50/60 Hz
Input Connectors	Power IEC 60320 C14
Power Output Connectors Details	4 x power IEC 60320 C13
Output Voltage	AC 220/230/240 V 57 - 63 Hz
Power Capacity	700 Watt / 1000 VA
Output Waveform	Sinewave
Surge Suppression	Yes
Surge Energy Rating	459 Joules
Circuit Protection	Circuit breaker

Battery

Technology	Lead Acid
Run Time (Up To)	8.5 min at full load
Recharge Time	3 hours
Features	Maintenance free, sealed, leak-proof

Networking

Remote Management Interface	Ethernet 10/100, RS-232, USB
Remote Management Protocol	SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, SSH, SSH-2

Expansion / Connectivity

Interfaces	1 x management (USB) - 4 pin USB Type B 1 x management (RS-232) - RJ-45 1 x management (Ethernet) - RJ-45
Expansion Slots	1 (total) / 1 (free) x SmartSlot

Miscellaneous

Cables Included	Serial cable USB cable
Rack Mounting Kit	Included
Features	Audible alarm, LCD display, Automatic Voltage Regulation (AVR), LED indicators
Compliant Standards	CSA, UL 1778, VDE, IEC 62040-2, EN 62040-2, EAC, RCM, IEC 62040-1, EN 62040-1

Software / System Requirements

Software Included	APC PowerChute Business Edition
Environmental Standards	
ENERGY STAR	Yes
Manufacturer Warranty	
Service & Support	Limited warranty - 3 years Limited warranty - batteries - 2 years
Environmental Parameters	
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	0 - 95%
Sound Emission	45 dBA
Dimensions & Weight	
Width	47.7 cm
Depth	43.2 cm
Height	8.6 cm
Weight	28.18 kg
Dimensions & Weight (Shipping)	
Shipping Width	59.4 cm
Shipping Depth	60.3 cm
Shipping Height	25.1 cm
Shipping Weight	31.45 kg
Compatibility Information	
Designed For	P/N: ACCS1000, ACCS1001, ACCS1002, ACCS1003, ACCS1004, ACCS1005, ACCS1006, ACCS1007, ACDC1015, ACDC1016, ACDC1017, ACDC1019, ACDC1020, ACDC1021, ACDC2513, ACF001, ACF002, ACF003, ACF101BLK, ACF102BLK, ACF201BLK, ACF400, ACF600, AP5017, AP5602, AP5606, AP5607, AP5616, AP92200, AP9290, AR100, AR100HD, AR202, AR203A, AR204A, AR2101, AR2102BLK, AR2144BLK, AR2145BLK, AR2200, AR2280, AR2400, AR2400FP1, AR2401, AR2407, AR2480, AR2487, AR2487G, AR2500, AR2507, AR2580, AR2587, AR2900, AR2901, AR3000, AR3100, AR3100G, AR3100SP, AR3100SP1, AR3100SP2, AR3100TAA, AR3100W, AR3100X609, AR3100X610, AR3100X617, AR3101, AR3104, AR3104SP1, AR3105, AR3105SP, AR3105W, AR3107, AR3107G, AR3107SP, AR3107X609, AR3107X610, AR3107X617, AR3130, AR3140, AR3140G, AR3140W, AR3150, AR3150SP, AR3150SP1, AR3150SP2, AR3150W, AR3150X609, AR3150X610, AR3150X617, AR3155, AR3155SP, AR3155W, AR3157, AR3157SP, AR3157X609, AR3157X610, AR3157X617, AR3200, AR3300, AR3300G, AR3300SP, AR3300W, AR3300X609, AR3300X610, AR3300X617, AR3305, AR3305SP, AR3305W, AR3307, AR3307SP, AR3307W, AR3307X609, AR3307X610, AR3307X617, AR3340, AR3340G, AR3340W, AR3347, AR3350, AR3350SP, AR3350W, AR3350X609, AR3350X610, AR3350X617, AR3355, AR3355SP, AR3355W, AR3357, AR3357SP, AR3357X609, AR3357X610, AR3357X617, AR4018, AR4018A, AR4018I, AR4018IA, AR4018IX429, AR4018IX431, AR4018IX432, AR4018SP, AR4018SPX429, AR4018SPX431, AR4018SPX432, AR4018X429, AR4018X431, AR4018X432, AR4024, AR4024A, AR4024I, AR4024IA, AR4024IX429, AR4024IX431, AR4024IX432, AR4024SP, AR4024SPX429, AR4024SPX431, AR4024SPX432, AR4024X429, AR4024X431, AR4024X432, AR4038, AR4038A, AR4038I, AR4038IA, AR4038IX429, AR4038IX431, AR4038IX432, AR4038X429, AR4038X432, AR7007, AR7050, AR7057, NBWL0356A

Technical data © 1WorldSync. Subject to technical modifications and errors.