

Dell PowerEdge T350 - Server - tower

1-way - 1 x Xeon E-2336 / 2.9 GHz - RAM 16 GB - SAS - hot-swap 3.5" bay(s) - SSD 2 x 480 GB - no graphics - GigE - no OS - monitor: none - black - BTP - with 3 Years ProSupport

Group	Servers
Manufacturer	Dell
Manufacturer item no.	VNXJC
EAN/UPC	5397184745687



Description

Affordably address common business workloads while delivering powerful compute with an entry-level 1U tower server.

Main features

Product Description	Dell PowerEdge T350 - tower - Xeon E-2336 2.9 GHz - 16 GB - SSD 2 x 480 GB
Type	Server - tower
Bundled Services	3 Years ProSupport
Server Scalability	1-way
Processor	1 x Intel Xeon E-2336 / 2.9 GHz (4.8 GHz) (6-core)
Processor Socket	FCLGA1200 Socket
Processor Main Features	Intel Turbo Boost Technology 2
Cache Memory	12 MB
Cache Per Processor	12 MB
RAM	16 GB (installed) / 128 GB (max) - DDR4 SDRAM - ECC
Storage Controller	RAID (PERC H755)
Server Storage Bays	Hot-swap 3.5"
Hard Drive	2 x SSD 480 GB (hot-swap) - SATA 6Gb/s
Optical Storage	No optical drive
Graphics Controller	No graphics
Networking	GigE
Power	(50/60 Hz)
Power Redundancy	Optional
OS Provided	No operating system
Colour	Black
Dimensions (WxDxH)	17.5 cm x 58.112 cm x 38.25 cm
Weight	25.34 kg
Pricing Type	Build To Plan (BTP)

Extended details

	General
Type	Server
Bundled Services	3 Years ProSupport
Product Form Factor	Tower
Server Scalability	1-way
Hot-Swap Bays Qty	8
Colour	Black
	Processor / Chipset
CPU	Intel Xeon E-2336
Clock Speed	2.9 GHz
Max Turbo Speed	4.8 GHz
Number of Cores	6-core
CPU Qty	1
Max CPU Qty	1
Processor Main Features	Intel Turbo Boost Technology 2
CPU Socket	FCLGA1200 Socket
	Cache Memory
Installed Size	12 MB
Cache Per Processor	12 MB
	RAM
Installed Size	16 GB / 128 GB (max)
Technology	DDR4 SDRAM - ECC
Effective Memory Speed	3200 MHz
Rated Memory Speed	3200 MHz
Form Factor	DIMM 288-pin
Slots	4 (Total) / 3 (empty)
Features	Unbuffered
Configuration Features	1 x 16 GB
	Hard Drive
Type	SSD - hot-swap
Capacity	2 x 480 GB
Interface Type	SATA 6Gb/s
Features	Read Intensive
	Storage Controller
Type	1 x RAID
Storage Controller Name	PERC H755
	Optical Storage
Type	No optical drive
	Monitor

Monitor Type	None.
Graphics Controller	
Graphics Processor	No graphics
Networking	
Interface (Bus) Type	LAN-on-motherboard (LOM)
Ethernet Ports	2 x Gigabit Ethernet
Ethernet Controller	Broadcom BCM5720
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Controller	Integrated Dell Remote Access Controller 9 Enterprise 15G (iDRAC9 15G)
Expansion / Connectivity	
Bays	8 (total) / 7 (free) x hot-swap 3.5"
Slots	1 (total) / 1 (free) x PCIe 4.0 x8 - half-length, full-height (x4 mode) ¦ 1 (total) / 1 (free) x PCIe 4.0 x16 - full-length, full-height ¦ 1 (total) / 1 (free) x PCIe 3.0 x1 - half-length, full-height ¦ 1 (total) / 1 (free) x PCIe 3.0 x8 - half-length, full-height (x4 mode)
Interfaces	2 x LAN (Gigabit Ethernet) ¦ 5 x USB 2.0 ¦ 2 x USB 3.0 (1 front, 1 rear) ¦ 1 x VGA - DB-15 ¦ 1 x management - micro-USB (1 in front) (iDRAC Direct port) ¦ 1 x serial - DB-9
Miscellaneous	
Included Accessories	Bezel
Pricing Type	Build To Plan (BTP)
Power	
Device Type	Power supply - hot-plug
Power Redundancy	Optional
Power Redundancy Scheme	1+1 (with optional power supply)
Installed Qty	1
Max Supported Qty	2
Voltage Required	AC 100-240 V (50/60 Hz)
Power Provided	600 Watt
Operating System / Software	
OS Provided	No operating system
Dimensions & Weight	
Width	17.5 cm
Depth	58.112 cm
Height	38.25 cm
Weight	25.34 kg

Technical data © 1WorldSync. Subject to technical modifications and errors.